

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1257917

Luminaire Tested: P3AS17R609040DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1257917
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-15)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R609040DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R60 optic, 4000K CCT AND, 90CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1660.0 lumens
Efficiency: N/A
Efficacy: 78.3 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1257917

CATALOG NUMBER: P3AS17R609040DE010 E3D1H

Luminous Intensity Polar Plot





TEST NUMBER: P1257917

CATALOG NUMBER: P3AS17R609040DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					30					10					0
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	114	111	109	106		111	109	107	105		105	103	102		101	100	99		98	97	96
2	108	104	100	96		106	102	98	95		99	96	93		96	93	91		93	91	89
3	103	97	92	88		101	96	91	88		93	89	86		91	87	85		88	86	84
4	98	91	85	81		96	90	85	81		88	83	80		86	82	79		84	81	78
5	93	85	80	75		92	84	79	75		83	78	74		81	77	74		79	76	73
6	89	80	74	70		87	79	74	70		78	73	70		77	72	69		75	71	69
7	85	76	70	66		83	75	69	65		74	69	65		72	68	65		71	67	64
8	81	71	65	61		79	71	65	61		70	65	61		69	64	61		68	64	61
9	77	67	62	58		76	67	61	58		66	61	57		65	61	57		64	60	57
10	73	64	58	54		72	63	58	54		63	58	54		62	57	54		61	57	54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	434943
5°	410587
10°	399926
15°	390785
20°	363355
25°	324817
30°	248114
35°	143242
40°	55590
45°	23165
50°	5083
55°	765
60°	614
65°	363
70°	449
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 23165 cd/sqm

TEST NUMBER: P1257917

CATALOG NUMBER: P3AS17R609040DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	176.1	10.6
10°-20°	479.5	28.9
20°-30°	600.6	36.2
30°-40°	335.7	20.2
40°-50°	63.8	3.8
50°-60°	3.3	0.2
60°-70°	0.8	0.0
70°-80°	0.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1256.2	75.7
0°-40°	1591.9	95.9
0°-60°	1659.0	99.9
0°-90°	1660.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1660.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1984	
5°	1865	176
15°	1721	480
25°	1342	601
35°	535	336
45°	75	64
55°	2	3
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1257917

CATALOG NUMBER: P3AS17R609040DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1983.5
1°	1975.4
2°	1949.5
3°	1919.0
4°	1890.5
5°	1865.3
6°	1846.3
7°	1830.0
8°	1817.8
9°	1806.3
10°	1796.1
11°	1785.9
12°	1774.4
13°	1760.1
14°	1743.1
15°	1721.4
16°	1694.9
17°	1665.0
18°	1631.1
19°	1592.4
20°	1557.1
21°	1519.0
22°	1479.6
23°	1438.2
24°	1392.7
25°	1342.5
26°	1283.4
27°	1217.5
28°	1143.5
29°	1064.7
30°	979.9
31°	894.3
32°	806.0
32.5°	757.8
33°	714.4
34°	624.0
35°	535.1
36°	455.0
37°	370.1
37.5°	331.4
38°	293.3
39°	236.3
40°	194.2
42.5°	118.2
45°	74.7

TEST NUMBER: P1257917

CATALOG NUMBER: P3AS17R609040DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	41.4
50°	14.9
52.5°	3.4
55°	2.0
57.5°	1.4
60°	1.4
62.5°	0.7
65°	0.7
67.5°	0.7
70°	0.7
72.5°	0.7
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)