

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1257954

Luminaire Tested: P3AS17R659040DE010 E3DL1MW

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1257954
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-43)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R659040DE010 E3DL1MW
Description: 3in Adjustable LED luminaire with, R65 optic, 4000K CCT AND, 90CRI , E3DL1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1389.1 lumens
Efficiency: N/A
Efficacy: 65.5 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1257954

CATALOG NUMBER: P3AS17R659040DE010 E3DL1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1257954

CATALOG NUMBER: P3AS17R659040DE010 E3DL1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	106	103	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	95	89	85	99	93	88	84	90	86	83		88	85	82		86
4	96	88	82	78	94	87	81	77	85	80	76		83	79	75		81
5	91	82	76	71	89	81	75	71	79	74	70		77	73	70		76
6	86	77	70	66	84	76	70	66	74	69	65		73	68	65		72
7	82	72	66	61	80	71	65	61	70	64	61		69	64	60		67
8	77	67	61	57	76	67	61	57	66	60	57		65	60	56		64
9	74	64	57	53	72	63	57	53	62	57	53		61	56	53		60
10	70	60	54	50	69	59	54	50	59	53	50		58	53	50		57

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	327561
5°	323640
10°	311350
15°	291670
20°	262336
25°	222763
30°	174229
35°	124156
40°	81238
45°	50238
50°	25517
55°	8984
60°	7894
65°	7887
70°	7117
75°	7032
80°	6945
85°	7045

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 50238 cd/sqm

TEST NUMBER: P1257954

CATALOG NUMBER: P3AS17R659040DE010 E3DL1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	138.0	9.9
10°-20°	357.6	25.7
20°-30°	417.9	30.1
30°-40°	292.0	21.0
40°-50°	128.6	9.3
50°-60°	28.6	2.1
60°-70°	14.6	1.0
70°-80°	8.8	0.6
80°-90°	3.0	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	913.5	65.8
0°-40°	1205.5	86.8
0°-60°	1362.7	98.1
0°-90°	1389.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1389.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1494	
5°	1470	138
15°	1285	358
25°	921	418
35°	464	292
45°	162	129
55°	24	29
65°	15	15
75°	8	9
85°	3	3
90°	0	

TEST NUMBER: P1257954

CATALOG NUMBER: P3AS17R659040DE010 E3DL1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	1493.8
2.5°	1488.3
5°	1470.3
7.5°	1439.8
10°	1398.3
12.5°	1347.1
15°	1284.8
17.5°	1208.6
20°	1124.2
22.5°	1028.6
25°	920.7
27.5°	807.1
30°	688.1
32.5°	573.2
35°	463.8
37.5°	368.3
40°	283.8
42.5°	214.6
45°	162.0
47.5°	119.1
50°	74.8
52.5°	38.8
55°	23.5
57.5°	20.8
60°	18.0
62.5°	16.6
65°	15.2
67.5°	12.5
70°	11.1
72.5°	9.7
75°	8.3
77.5°	6.9
80°	5.5
82.5°	4.2
85°	2.8
87.5°	1.4
90°	0.0

(END OF REPORT)