

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1258265

Luminaire Tested: P3AS20R609040D010 E3D1WH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1258265
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-15)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R609040D010 E3D1WH
Description: 3in Adjustable LED luminaire with, R60 optic, 4000K CCT AND, 90CRI , E3D1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2179.0 lumens
Efficiency: N/A
Efficacy: 75.7 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1258265

CATALOG NUMBER: P3AS20R609040D010 E3D1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1258265

CATALOG NUMBER: P3AS20R609040D010 E3D1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	96	91	88	93	89	86		91	87	85		88
4	98	91	85	81	96	90	85	81	88	83	80		86	82	79		84
5	93	85	80	75	92	84	79	75	83	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	70		77	72	69		75
7	85	76	70	66	83	75	69	65	74	69	65		72	68	65		71
8	81	71	65	61	79	71	65	61	70	65	61		69	64	61		68
9	77	67	62	58	76	67	61	58	66	61	57		65	61	57		64
10	73	64	58	54	72	63	58	54	63	58	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	570919
5°	538960
10°	524951
15°	512965
20°	476951
25°	426363
30°	325670
35°	188027
40°	72965
45°	30391
50°	6686
55°	1032
60°	789
65°	467
70°	577
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 30391 cd/sqm

TEST NUMBER: P1258265

CATALOG NUMBER: P3AS20R609040D010 E3D1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	231.1	10.6
10°-20°	629.4	28.9
20°-30°	788.3	36.2
30°-40°	440.7	20.2
40°-50°	83.8	3.8
50°-60°	4.3	0.2
60°-70°	1.0	0.0
70°-80°	0.4	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1648.9	75.7
0°-40°	2089.6	95.9
0°-60°	2177.7	99.9
0°-90°	2179.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2179.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2604	
5°	2448	231
15°	2260	629
25°	1762	788
35°	702	441
45°	98	84
55°	3	4
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1258265

CATALOG NUMBER: P3AS20R609040D010 E3D1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	2603.6
1°	2592.9
2°	2559.1
3°	2519.0
4°	2481.5
5°	2448.5
6°	2423.6
7°	2402.2
8°	2386.2
9°	2371.0
10°	2357.6
11°	2344.3
12°	2329.1
13°	2310.4
14°	2288.1
15°	2259.6
16°	2224.8
17°	2185.6
18°	2141.0
19°	2090.2
20°	2043.9
21°	1994.0
22°	1942.3
23°	1887.9
24°	1828.2
25°	1762.2
26°	1684.7
27°	1598.2
28°	1501.0
29°	1397.6
30°	1286.2
31°	1173.9
32°	1058.0
32.5°	994.8
33°	937.7
34°	819.2
35°	702.4
36°	597.2
37°	485.8
37.5°	435.0
38°	385.1
39°	310.2
40°	254.9
42.5°	155.1
45°	98.0



TEST NUMBER: P1258265

CATALOG NUMBER: P3AS20R609040D010 E3D1WH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	54.4
50°	19.6
52.5°	4.5
55°	2.7
57.5°	1.8
60°	1.8
62.5°	0.9
65°	0.9
67.5°	0.9
70°	0.9
72.5°	0.9
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)