

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1258309

Luminaire Tested: P3AS20R659040D010 E3DLP1H

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1258309  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-41)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS20R659040D010 E3DLP1H  
Description: 3in Adjustable LED luminaire with, R65 optic, 4000K CCT AND, 90CRI , E3DLP1H TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1259.9 lumens  
Efficiency: N/A  
Efficacy: 43.7 lumens/watt  
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 28.8  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1258309

CATALOG NUMBER: P3AS20R659040D010 E3DLP1H

### Luminous Intensity Polar Plot



TEST NUMBER: P1258309

CATALOG NUMBER: P3AS20R659040D010 E3DLP1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 107 | 105 | 110 | 108 | 105 | 103 | 104 | 102 | 100 |  | 100 | 98  | 97  |  | 96  |
| 2   | 107 | 101 | 97  | 93  | 104 | 100 | 96  | 92  | 96  | 93  | 90  |  | 93  | 91  | 88  |  | 90  |
| 3   | 101 | 94  | 88  | 84  | 99  | 92  | 87  | 83  | 90  | 85  | 82  |  | 87  | 84  | 81  |  | 85  |
| 4   | 95  | 87  | 81  | 76  | 93  | 86  | 80  | 76  | 84  | 79  | 75  |  | 82  | 78  | 74  |  | 80  |
| 5   | 90  | 81  | 75  | 70  | 88  | 80  | 74  | 70  | 78  | 73  | 69  |  | 77  | 72  | 69  |  | 75  |
| 6   | 85  | 76  | 69  | 65  | 84  | 75  | 69  | 65  | 73  | 68  | 64  |  | 72  | 67  | 64  |  | 71  |
| 7   | 81  | 71  | 65  | 60  | 79  | 70  | 64  | 60  | 69  | 64  | 60  |  | 68  | 63  | 59  |  | 67  |
| 8   | 77  | 67  | 60  | 56  | 75  | 66  | 60  | 56  | 65  | 59  | 56  |  | 64  | 59  | 55  |  | 63  |
| 9   | 73  | 63  | 57  | 52  | 72  | 62  | 56  | 52  | 61  | 56  | 52  |  | 60  | 55  | 52  |  | 59  |
| 10  | 69  | 59  | 53  | 49  | 68  | 59  | 53  | 49  | 58  | 53  | 49  |  | 57  | 52  | 49  |  | 56  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 320281 |
| 5°  | 312304 |
| 10° | 290821 |
| 15° | 260637 |
| 20° | 225093 |
| 25° | 187245 |
| 30° | 147643 |
| 35° | 109406 |
| 40° | 75398  |
| 45° | 46765  |
| 50° | 25415  |
| 55° | 15980  |
| 60° | 13552  |
| 65° | 12245  |
| 70° | 10450  |
| 75° | 9235   |
| 80° | 9218   |
| 85° | 9057   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 46765 cd/sqm

TEST NUMBER: P1258309

CATALOG NUMBER: P3AS20R659040D010 E3DLP1H

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 131.8  | 10.5      |
| 10°-20°   | 319.1  | 25.3      |
| 20°-30°   | 352.8  | 28.0      |
| 30°-40°   | 256.3  | 20.3      |
| 40°-50°   | 120.1  | 9.5       |
| 50°-60°   | 40.4   | 3.2       |
| 60°-70°   | 23.3   | 1.9       |
| 70°-80°   | 12.2   | 1.0       |
| 80°-90°   | 3.9    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 803.7  | 63.8      |
| 0°-40°    | 1060.0 | 84.1      |
| 0°-60°    | 1220.5 | 96.9      |
| 0°-90°    | 1259.9 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 1259.9 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 1461 |      |
| 5°  | 1419 | 132  |
| 15° | 1148 | 319  |
| 25° | 774  | 353  |
| 35° | 409  | 256  |
| 45° | 151  | 120  |
| 55° | 42   | 40   |
| 65° | 24   | 23   |
| 75° | 11   | 12   |
| 85° | 4    | 4    |
| 90° | 0    |      |

TEST NUMBER: P1258309

CATALOG NUMBER: P3AS20R659040D010 E3DLP1H

**CANDELA DISTRIBUTION (FULL):**

| 0°    |        |
|-------|--------|
| 0°    | 1460.6 |
| 2.5°  | 1451.5 |
| 5°    | 1418.8 |
| 7.5°  | 1369.7 |
| 10°   | 1306.1 |
| 12.5° | 1231.7 |
| 15°   | 1148.1 |
| 17.5° | 1057.3 |
| 20°   | 964.6  |
| 22.5° | 868.3  |
| 25°   | 773.9  |
| 27.5° | 677.6  |
| 30°   | 583.1  |
| 32.5° | 492.3  |
| 35°   | 408.7  |
| 37.5° | 332.4  |
| 40°   | 263.4  |
| 42.5° | 201.6  |
| 45°   | 150.8  |
| 47.5° | 109.0  |
| 50°   | 74.5   |
| 52.5° | 50.9   |
| 55°   | 41.8   |
| 57.5° | 36.3   |
| 60°   | 30.9   |
| 62.5° | 27.2   |
| 65°   | 23.6   |
| 67.5° | 20.0   |
| 70°   | 16.3   |
| 72.5° | 14.5   |
| 75°   | 10.9   |
| 77.5° | 9.1    |
| 80°   | 7.3    |
| 82.5° | 5.4    |
| 85°   | 3.6    |
| 87.5° | 1.8    |
| 90°   | 0.0    |

(END OF REPORT)