

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1258498

Luminaire Tested: P3AS24R409040D010 E3D1WH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1258498
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-12)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS24R409040D010 E3D1WH
Description: 3in Adjustable LED luminaire with, R40 optic, 4000K CCT AND, 90CRI , E3D1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2909.0 lumens
Efficiency: N/A
Efficacy: 101.0 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.6
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1258498

CATALOG NUMBER: P3AS24R409040D010 E3D1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1258498

CATALOG NUMBER: P3AS24R409040D010 E3D1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	109	112	110	109	107	106	105	104		103	102	101		99
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		96
3	107	102	98	95	105	100	97	94	98	95	93		96	93	91		93
4	103	97	93	90	101	96	92	89	94	91	88		92	89	87		90
5	99	93	89	85	98	92	88	85	91	87	84		89	86	84		88
6	96	89	85	81	95	89	84	81	87	83	81		86	83	80		85
7	93	86	81	78	92	85	81	78	84	80	77		83	80	77		82
8	90	83	78	75	89	82	78	75	81	77	75		80	77	74		79
9	87	80	75	72	86	79	75	72	78	75	72		78	74	72		77
10	84	77	72	70	83	77	72	69	76	72	69		75	72	69		74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1482776
5°	1472085
10°	1433552
15°	1280552
20°	849104
25°	318091
30°	85102
35°	33247
40°	11965
45°	5675
50°	1740
55°	765
60°	439
65°	519
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 5675 cd/sqm

TEST NUMBER: P1258498

CATALOG NUMBER: P3AS24R409040D010 E3D1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	631.1	21.7
10°-20°	1494.6	51.4
20°-30°	677.8	23.3
30°-40°	87.8	3.0
40°-50°	15.2	0.5
50°-60°	1.8	0.1
60°-70°	0.6	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2803.5	96.4
0°-40°	2891.4	99.4
0°-60°	2908.4	100.0
0°-90°	2909.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2909.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6762	
5°	6688	631
15°	5641	1495
25°	1315	678
35°	124	88
45°	18	15
55°	2	2
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1258498

CATALOG NUMBER: P3AS24R409040D010 E3D1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	6762.0
1°	6758.0
2°	6747.8
3°	6732.5
4°	6713.2
5°	6687.7
6°	6658.2
7°	6621.5
8°	6576.7
9°	6515.6
10°	6438.2
11°	6347.6
12°	6226.4
13°	6076.7
14°	5881.1
15°	5640.8
16°	5334.3
17°	4985.0
18°	4565.4
19°	4122.4
20°	3638.7
21°	3154.9
22°	2678.3
23°	2203.8
24°	1737.4
25°	1314.7
26°	973.6
27°	712.9
28°	535.7
29°	416.5
30°	336.1
31°	278.0
32°	232.2
32.5°	211.8
33°	191.5
34°	155.8
35°	124.2
36°	97.8
37°	77.4
37.5°	69.2
38°	61.1
39°	50.9
40°	41.8
42.5°	27.5
45°	18.3

TEST NUMBER: P1258498

CATALOG NUMBER: P3AS24R409040D010 E3D1WH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	11.2
50°	5.1
52.5°	2.0
55°	2.0
57.5°	1.0
60°	1.0
62.5°	1.0
65°	1.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)