

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1259434

Luminaire Tested: P3AS05R659050DE010 E3DLP1LI

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1259434  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-41)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS05R659050DE010 E3DLP1LI  
Description: 3in Adjustable LED luminaire with, R65 optic, 5000K CCT AND, 90CRI , E3DLP1LI TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 379.0 lumens  
Efficiency: N/A  
Efficacy: 52.6 lumens/watt  
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 7.2  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1259434

CATALOG NUMBER: P3AS05R659050DE010 E3DLP1LI

### Luminous Intensity Polar Plot



TEST NUMBER: P1259434

CATALOG NUMBER: P3AS05R659050DE010 E3DLP1LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 107 | 105 | 110 | 108 | 105 | 103 | 104 | 102 | 100 |  | 100 | 98  | 97  |  | 96  |
| 2   | 107 | 101 | 97  | 93  | 104 | 100 | 96  | 92  | 96  | 93  | 90  |  | 93  | 91  | 88  |  | 90  |
| 3   | 101 | 94  | 88  | 84  | 99  | 92  | 87  | 83  | 90  | 85  | 82  |  | 87  | 84  | 81  |  | 85  |
| 4   | 95  | 87  | 81  | 76  | 93  | 86  | 80  | 76  | 84  | 79  | 75  |  | 82  | 78  | 74  |  | 80  |
| 5   | 90  | 81  | 75  | 70  | 88  | 80  | 74  | 70  | 78  | 73  | 69  |  | 77  | 72  | 69  |  | 75  |
| 6   | 85  | 76  | 69  | 65  | 84  | 75  | 69  | 65  | 73  | 68  | 64  |  | 72  | 67  | 64  |  | 71  |
| 7   | 81  | 71  | 65  | 60  | 79  | 70  | 64  | 60  | 69  | 64  | 60  |  | 68  | 63  | 59  |  | 67  |
| 8   | 77  | 67  | 60  | 56  | 75  | 66  | 60  | 56  | 65  | 59  | 56  |  | 64  | 59  | 55  |  | 63  |
| 9   | 73  | 63  | 57  | 52  | 72  | 62  | 56  | 52  | 61  | 56  | 52  |  | 60  | 55  | 52  |  | 59  |
| 10  | 69  | 59  | 53  | 49  | 68  | 59  | 53  | 49  | 58  | 53  | 49  |  | 57  | 52  | 49  |  | 56  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |       |
|-----|-------|
|     | 0°    |
| 0°  | 96330 |
| 5°  | 93946 |
| 10° | 87484 |
| 15° | 78389 |
| 20° | 67719 |
| 25° | 56326 |
| 30° | 44412 |
| 35° | 32899 |
| 40° | 22671 |
| 45° | 14079 |
| 50° | 7642  |
| 55° | 4817  |
| 60° | 4079  |
| 65° | 3684  |
| 70° | 3142  |
| 75° | 2796  |
| 80° | 2778  |
| 85° | 2768  |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 14079 cd/sqm

TEST NUMBER: P1259434

CATALOG NUMBER: P3AS05R659050DE010 E3DLP1LI

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 39.7   | 10.5      |
| 10°-20°   | 96.0   | 25.3      |
| 20°-30°   | 106.1  | 28.0      |
| 30°-40°   | 77.1   | 20.3      |
| 40°-50°   | 36.1   | 9.5       |
| 50°-60°   | 12.2   | 3.2       |
| 60°-70°   | 7.0    | 1.9       |
| 70°-80°   | 3.7    | 1.0       |
| 80°-90°   | 1.2    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 241.8  | 63.8      |
| 0°-40°    | 318.8  | 84.1      |
| 0°-60°    | 367.1  | 96.9      |
| 0°-90°    | 379.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 379.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 439 |      |
| 5°  | 427 | 40   |
| 15° | 345 | 96   |
| 25° | 233 | 106  |
| 35° | 123 | 77   |
| 45° | 45  | 36   |
| 55° | 13  | 12   |
| 65° | 7   | 7    |
| 75° | 3   | 4    |
| 85° | 1   | 1    |
| 90° | 0   |      |

TEST NUMBER: P1259434

CATALOG NUMBER: P3AS05R659050DE010 E3DLP1LI

**CANDELA DISTRIBUTION (FULL):**

|       | 0°    |
|-------|-------|
| 0°    | 439.3 |
| 2.5°  | 436.6 |
| 5°    | 426.8 |
| 7.5°  | 412.0 |
| 10°   | 392.9 |
| 12.5° | 370.5 |
| 15°   | 345.3 |
| 17.5° | 318.0 |
| 20°   | 290.2 |
| 22.5° | 261.2 |
| 25°   | 232.8 |
| 27.5° | 203.8 |
| 30°   | 175.4 |
| 32.5° | 148.1 |
| 35°   | 122.9 |
| 37.5° | 100.0 |
| 40°   | 79.2  |
| 42.5° | 60.7  |
| 45°   | 45.4  |
| 47.5° | 32.8  |
| 50°   | 22.4  |
| 52.5° | 15.3  |
| 55°   | 12.6  |
| 57.5° | 10.9  |
| 60°   | 9.3   |
| 62.5° | 8.2   |
| 65°   | 7.1   |
| 67.5° | 6.0   |
| 70°   | 4.9   |
| 72.5° | 4.4   |
| 75°   | 3.3   |
| 77.5° | 2.7   |
| 80°   | 2.2   |
| 82.5° | 1.6   |
| 85°   | 1.1   |
| 87.5° | 0.5   |
| 90°   | 0.0   |

(END OF REPORT)