

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1259953

Luminaire Tested: P3AS13R259050DE010 E3DLP1LI

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1259953  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-9)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS13R259050DE010 E3DLP1LI  
Description: 3in Adjustable LED luminaire with, R25 optic, 5000K CCT AND, 90CRI , E3DLP1LI TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 681.0 lumens  
Efficiency: N/A  
Efficacy: 46.6 lumens/watt  
Spacing Criteria (0/90/45): 0.62 / 0.62 / 0.68  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 14.6  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1259953

CATALOG NUMBER: P3AS13R259050DE010 E3DLP1LI

### Luminous Intensity Polar Plot





TEST NUMBER: P1259953

CATALOG NUMBER: P3AS13R259050DE010 E3DLP1LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 108 | 105 | 111 | 108 | 106 | 104 | 104 | 102 | 101 |  | 100 | 99  | 98  |  | 97  |
| 2   | 107 | 102 | 98  | 95  | 105 | 101 | 97  | 94  | 97  | 94  | 92  |  | 94  | 92  | 90  |  | 92  |
| 3   | 102 | 95  | 90  | 86  | 100 | 94  | 89  | 86  | 91  | 87  | 84  |  | 89  | 86  | 83  |  | 87  |
| 4   | 97  | 89  | 84  | 79  | 95  | 88  | 83  | 79  | 86  | 81  | 78  |  | 84  | 80  | 77  |  | 82  |
| 5   | 92  | 84  | 78  | 74  | 91  | 83  | 77  | 73  | 81  | 76  | 73  |  | 79  | 75  | 72  |  | 78  |
| 6   | 88  | 79  | 73  | 69  | 86  | 78  | 72  | 68  | 77  | 72  | 68  |  | 75  | 71  | 67  |  | 74  |
| 7   | 84  | 74  | 68  | 64  | 82  | 74  | 68  | 64  | 72  | 67  | 64  |  | 71  | 67  | 63  |  | 70  |
| 8   | 80  | 70  | 65  | 60  | 79  | 70  | 64  | 60  | 69  | 64  | 60  |  | 68  | 63  | 60  |  | 67  |
| 9   | 76  | 67  | 61  | 57  | 75  | 66  | 61  | 57  | 65  | 60  | 57  |  | 65  | 60  | 57  |  | 64  |
| 10  | 73  | 64  | 58  | 54  | 72  | 63  | 58  | 54  | 62  | 57  | 54  |  | 62  | 57  | 54  |  | 61  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 247239 |
| 5°  | 237199 |
| 10° | 207790 |
| 15° | 167016 |
| 20° | 128344 |
| 25° | 97094  |
| 30° | 70163  |
| 35° | 46605  |
| 40° | 28253  |
| 45° | 16467  |
| 50° | 10507  |
| 55° | 8525   |
| 60° | 7456   |
| 65° | 6590   |
| 70° | 5450   |
| 75° | 5422   |
| 80° | 4041   |
| 85° | 5284   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 16467 cd/sqm

TEST NUMBER: P1259953

CATALOG NUMBER: P3AS13R259050DE010 E3DLP1LI

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 98.1   | 14.4      |
| 10°-20°   | 203.5  | 29.9      |
| 20°-30°   | 184.0  | 27.0      |
| 30°-40°   | 110.5  | 16.2      |
| 40°-50°   | 43.9   | 6.4       |
| 50°-60°   | 20.3   | 3.0       |
| 60°-70°   | 12.3   | 1.8       |
| 70°-80°   | 6.6    | 1.0       |
| 80°-90°   | 1.9    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 485.5  | 71.3      |
| 0°-40°    | 596.1  | 87.5      |
| 0°-60°    | 660.2  | 96.9      |
| 0°-90°    | 681.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 681.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 1128 |      |
| 5°  | 1078 | 98   |
| 15° | 736  | 203  |
| 25° | 401  | 184  |
| 35° | 174  | 111  |
| 45° | 53   | 44   |
| 55° | 22   | 20   |
| 65° | 13   | 12   |
| 75° | 6    | 7    |
| 85° | 2    | 2    |
| 90° | 0    |      |

TEST NUMBER: P1259953

CATALOG NUMBER: P3AS13R259050DE010 E3DLP1LI

**CANDELA DISTRIBUTION (FULL):**

| 0°    |        |
|-------|--------|
| 0°    | 1127.5 |
| 1°    | 1127.5 |
| 2°    | 1122.2 |
| 3°    | 1110.5 |
| 4°    | 1095.7 |
| 5°    | 1077.6 |
| 6°    | 1054.3 |
| 7°    | 1027.7 |
| 8°    | 996.9  |
| 9°    | 966.1  |
| 10°   | 933.2  |
| 11°   | 895.0  |
| 12°   | 855.7  |
| 13°   | 816.4  |
| 14°   | 777.2  |
| 15°   | 735.7  |
| 17.5° | 638.1  |
| 20°   | 550.0  |
| 22.5° | 470.3  |
| 25°   | 401.3  |
| 27.5° | 336.6  |
| 30°   | 277.1  |
| 32.5° | 223.0  |
| 35°   | 174.1  |
| 37.5° | 132.7  |
| 40°   | 98.7   |
| 42.5° | 72.2   |
| 45°   | 53.1   |
| 47.5° | 40.3   |
| 50°   | 30.8   |
| 52.5° | 25.5   |
| 55°   | 22.3   |
| 57.5° | 19.1   |
| 60°   | 17.0   |
| 62.5° | 13.8   |
| 65°   | 12.7   |
| 67.5° | 10.6   |
| 70°   | 8.5    |
| 72.5° | 7.4    |
| 75°   | 6.4    |
| 77.5° | 5.3    |
| 80°   | 3.2    |
| 82.5° | 2.1    |
| 85°   | 2.1    |
| 87.5° | 1.1    |



TEST NUMBER: P1259953

CATALOG NUMBER: P3AS13R259050DE010 E3DLP1LI

CANDELA DISTRIBUTION (continued):

0°  
90° | 0.0

(END OF REPORT)