

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1260030

Luminaire Tested: P3AS13R409050DE010 E3D1WMH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1260030
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-12)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R409050DE010 E3D1WMH
Description: 3in Adjustable LED luminaire with, R40 optic, 5000K CCT AND, 90CRI , E3D1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1485.9 lumens
Efficiency: N/A
Efficacy: 101.8 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.6
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1260030

CATALOG NUMBER: P3AS13R409050DE010 E3D1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1260030

CATALOG NUMBER: P3AS13R409050DE010 E3D1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	109	112	110	109	107	106	105	104		103	102	101		99
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		96
3	107	102	98	95	105	100	97	94	98	95	93		96	93	91		93
4	103	97	93	90	101	96	92	89	94	91	88		92	89	87		90
5	99	93	89	85	98	92	88	85	91	87	84		89	86	84		88
6	96	89	85	81	95	89	84	81	87	83	81		86	83	80		85
7	93	86	81	78	92	85	81	78	84	80	77		83	80	77		82
8	90	83	78	75	89	82	78	75	81	77	75		80	77	74		79
9	87	80	75	72	86	79	75	72	78	75	72		78	74	72		77
10	84	77	72	70	83	77	72	69	76	72	69		75	72	69		75

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	757439
5°	751990
10°	732296
15°	654147
20°	433734
25°	162493
30°	43475
35°	16998
40°	6097
45°	2915
50°	887
55°	382
60°	219
65°	259
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2915 cd/sqm

TEST NUMBER: P1260030

CATALOG NUMBER: P3AS13R409050DE010 E3D1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	322.4	21.7
10°-20°	763.5	51.4
20°-30°	346.2	23.3
30°-40°	44.9	3.0
40°-50°	7.8	0.5
50°-60°	0.9	0.1
60°-70°	0.3	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1432.1	96.4
0°-40°	1477.0	99.4
0°-60°	1485.6	100.0
0°-90°	1485.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1485.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3454	
5°	3416	322
15°	2882	763
25°	672	346
35°	64	45
45°	9	8
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1260030

CATALOG NUMBER: P3AS13R409050DE010 E3D1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	3454.2
1°	3452.2
2°	3447.0
3°	3439.2
4°	3429.3
5°	3416.3
6°	3401.2
7°	3382.5
8°	3359.6
9°	3328.3
10°	3288.8
11°	3242.5
12°	3180.6
13°	3104.1
14°	3004.3
15°	2881.5
16°	2724.9
17°	2546.5
18°	2332.1
19°	2105.8
20°	1858.7
21°	1611.6
22°	1368.2
23°	1125.7
24°	887.5
25°	671.6
26°	497.3
27°	364.2
28°	273.6
29°	212.8
30°	171.7
31°	142.0
32°	118.6
32.5°	108.2
33°	97.8
34°	79.6
35°	63.5
36°	49.9
37°	39.5
37.5°	35.4
38°	31.2
39°	26.0
40°	21.3
42.5°	14.0
45°	9.4



TEST NUMBER: P1260030

CATALOG NUMBER: P3AS13R409050DE010 E3D1WMH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	5.7
50°	2.6
52.5°	1.0
55°	1.0
57.5°	0.5
60°	0.5
62.5°	0.5
65°	0.5
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)