

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1260045

Luminaire Tested: P3AS13R409050DE010 E3DLP1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1260045
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-21)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R409050DE010 E3DLP1LI
Description: 3in Adjustable LED luminaire with, R40 optic, 5000K CCT AND, 90CRI , E3DLP1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 780.0 lumens
Efficiency: N/A
Efficacy: 53.4 lumens/watt
Spacing Criteria (0/90/45): 0.73 / 0.73 / 0.74
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1260045

CATALOG NUMBER: P3AS13R409050DE010 E3DLP1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1260045

CATALOG NUMBER: P3AS13R409050DE010 E3DLP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	95	105	101	97	93	97	94	91		94	92	89		92
3	102	95	90	86	100	94	89	85	91	87	84		89	85	83		86
4	97	89	83	79	95	88	83	79	86	81	78		84	80	77		82
5	92	83	77	73	90	82	77	73	81	76	72		79	75	71		77
6	87	78	72	68	86	78	72	68	76	71	67		75	70	67		73
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	75	66	60	56	65	60	56		64	59	56		63
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	242875
5°	237948
10°	221550
15°	193100
20°	155624
25°	116644
30°	82013
35°	53726
40°	32518
45°	19444
50°	11599
55°	9328
60°	8377
65°	7160
70°	6796
75°	5422
80°	5304
85°	5284

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 19444 cd/sqm

TEST NUMBER: P1260045

CATALOG NUMBER: P3AS13R409050DE010 E3DLP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	100.4	12.9
10°-20°	234.3	30.0
20°-30°	220.8	28.3
30°-40°	127.7	16.4
40°-50°	50.9	6.5
50°-60°	22.5	2.9
60°-70°	13.9	1.8
70°-80°	7.3	0.9
80°-90°	2.3	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	555.4	71.2
0°-40°	683.1	87.6
0°-60°	756.5	97.0
0°-90°	780.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	780.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1108	
5°	1081	100
15°	851	234
25°	482	221
35°	201	128
45°	63	51
55°	24	23
65°	14	14
75°	6	7
85°	2	2
90°	0	

TEST NUMBER: P1260045

CATALOG NUMBER: P3AS13R409050DE010 E3DLP1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	1107.6
2.5°	1101.2
5°	1081.0
7.5°	1043.9
10°	995.0
12.5°	929.2
15°	850.6
17.5°	762.5
20°	666.9
22.5°	571.3
25°	482.1
27.5°	399.3
30°	323.9
32.5°	258.0
35°	200.7
37.5°	151.9
40°	113.6
42.5°	85.0
45°	62.7
47.5°	45.7
50°	34.0
52.5°	27.6
55°	24.4
57.5°	22.3
60°	19.1
62.5°	15.9
65°	13.8
67.5°	11.7
70°	10.6
72.5°	8.5
75°	6.4
77.5°	5.3
80°	4.2
82.5°	3.2
85°	2.1
87.5°	1.1
90°	0.0

(END OF REPORT)