

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1260087

Luminaire Tested: P3AS13R509050DE010 E3DL1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1260087
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-31)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R509050DE010 E3DL1LI
Description: 3in Adjustable LED luminaire with, R50 optic, 5000K CCT AND, 90CRI , E3DL1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1194.0 lumens
Efficiency: N/A
Efficacy: 81.8 lumens/watt
Spacing Criteria (0/90/45): 0.77 / 0.77 / 0.75
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1260087

CATALOG NUMBER: P3AS13R509050DE010 E3DL1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1260087

CATALOG NUMBER: P3AS13R509050DE010 E3DL1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	102	98	95	98	95	93		95	93	91		93
3	103	97	92	88	101	95	91	87	93	89	86		90	87	84		88
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84
5	93	85	80	75	92	84	79	75	83	78	74		81	77	74		79
6	89	80	75	71	88	80	74	70	78	73	70		77	73	69		75
7	85	76	70	66	84	75	70	66	74	69	66		73	69	65		72
8	81	72	66	62	80	71	66	62	70	65	62		69	65	62		68
9	78	68	63	59	76	68	62	59	67	62	59		66	62	58		65
10	74	65	59	56	73	65	59	56	64	59	55		63	58	55		62

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	380145
5°	372484
10°	348891
15°	312351
20°	262850
25°	200600
30°	130374
35°	77310
40°	44684
45°	22390
50°	8324
55°	6499
60°	6052
65°	5500
70°	5450
75°	5422
80°	5304
85°	5284

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 22390 cd/sqm

TEST NUMBER: P1260087

CATALOG NUMBER: P3AS13R509050DE010 E3DL1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	157.4	13.2
10°-20°	380.5	31.9
20°-30°	373.3	31.3
30°-40°	188.1	15.8
40°-50°	59.4	5.0
50°-60°	15.4	1.3
60°-70°	10.9	0.9
70°-80°	6.7	0.6
80°-90°	2.3	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	911.2	76.3
0°-40°	1099.3	92.1
0°-60°	1174.1	98.3
0°-90°	1194.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1194.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1734	
5°	1692	157
15°	1376	380
25°	829	373
35°	289	188
45°	72	59
55°	17	15
65°	11	11
75°	6	7
85°	2	2
90°	0	

TEST NUMBER: P1260087

CATALOG NUMBER: P3AS13R509050DE010 E3DL1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	1733.6
2.5°	1723.0
5°	1692.2
7.5°	1637.0
10°	1566.9
12.5°	1476.7
15°	1375.9
17.5°	1259.1
20°	1126.4
22.5°	983.1
25°	829.1
27.5°	665.6
30°	514.9
32.5°	387.5
35°	288.8
37.5°	213.4
40°	156.1
42.5°	110.4
45°	72.2
47.5°	41.4
50°	24.4
52.5°	18.0
55°	17.0
57.5°	14.9
60°	13.8
62.5°	12.7
65°	10.6
67.5°	9.6
70°	8.5
72.5°	7.4
75°	6.4
77.5°	5.3
80°	4.2
82.5°	3.2
85°	2.1
87.5°	1.1
90°	0.0

(END OF REPORT)