

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1260109

Luminaire Tested: P3AS13R559050DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1260109
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-14)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R559050DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R55 optic, 5000K CCT AND, 90CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1370.0 lumens
Efficiency: N/A
Efficacy: 93.8 lumens/watt
Spacing Criteria (0/90/45): 0.93 / 0.93 / 0.82
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1260109

CATALOG NUMBER: P3AS13R559050DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1260109

CATALOG NUMBER: P3AS13R559050DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	112	109	107	105	105	104	102		102	100	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	104	98	94	90	102	97	93	90	95	91	88		92	89	87		90
4	100	93	88	84	98	92	87	84	90	86	83		88	84	82		86
5	95	88	83	79	94	87	82	78	85	81	78		84	80	77		82
6	91	83	78	74	90	82	77	74	81	76	73		80	76	73		78
7	87	79	73	70	86	78	73	69	77	72	69		76	72	69		75
8	83	75	69	66	82	74	69	66	73	69	65		72	68	65		71
9	80	71	66	62	79	71	66	62	70	65	62		69	65	62		68
10	77	68	62	59	76	67	62	59	67	62	59		66	62	59		65

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	397293
5°	383226
10°	396920
15°	391330
20°	362165
25°	292904
30°	175546
35°	59481
40°	16402
45°	7257
50°	2115
55°	382
60°	219
65°	259
70°	321
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 7257 cd/sqm

TEST NUMBER: P1260109

CATALOG NUMBER: P3AS13R559050DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	168.4	12.3
10°-20°	479.9	35.0
20°-30°	533.5	38.9
30°-40°	166.1	12.1
40°-50°	19.9	1.5
50°-60°	1.5	0.1
60°-70°	0.5	0.0
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1181.9	86.3
0°-40°	1347.9	98.4
0°-60°	1369.4	100.0
0°-90°	1370.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1370.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1812	
5°	1741	168
15°	1724	480
25°	1211	533
35°	222	166
45°	23	20
55°	1	2
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1260109

CATALOG NUMBER: P3AS13R559050DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1811.8
1°	1805.0
2°	1787.3
3°	1765.4
4°	1745.7
5°	1741.0
6°	1746.2
7°	1757.1
8°	1769.6
9°	1779.5
10°	1782.6
11°	1780.5
12°	1772.2
13°	1759.2
14°	1744.1
15°	1723.8
16°	1700.4
17°	1670.7
18°	1637.4
19°	1597.3
20°	1552.0
21°	1500.5
22°	1439.6
23°	1372.5
24°	1295.5
25°	1210.6
26°	1117.5
27°	1018.6
28°	912.9
29°	804.1
30°	693.3
31°	581.9
32°	473.1
32.5°	424.7
33°	374.7
34°	289.9
35°	222.2
36°	169.2
37°	125.4
37.5°	107.2
38°	93.2
39°	70.8
40°	57.3
42.5°	36.4
45°	23.4



TEST NUMBER: P1260109

CATALOG NUMBER: P3AS13R559050DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	14.1
50°	6.2
52.5°	2.1
55°	1.0
57.5°	0.5
60°	0.5
62.5°	0.5
65°	0.5
67.5°	0.5
70°	0.5
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)