

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1260139

Luminaire Tested: P3AS13R609050DE010 E3D1LI

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1260139
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-15)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R609050DE010 E3D1LI
Description: 3in Adjustable LED luminaire with, R60 optic, 5000K CCT AND, 90CRI , E3D1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1271.9 lumens
Efficiency: N/A
Efficacy: 87.1 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1260139

CATALOG NUMBER: P3AS13R609050DE010 E3D1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1260139

CATALOG NUMBER: P3AS13R609050DE010 E3D1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	96	91	88	93	89	86		91	87	85		88
4	98	91	85	81	96	90	85	81	88	83	80		86	82	79		84
5	93	85	80	75	92	84	79	75	83	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	70		77	72	69		75
7	85	76	70	66	83	75	69	65	74	69	65		72	68	65		71
8	81	71	65	61	79	71	65	61	70	65	61		69	64	61		68
9	77	67	62	58	76	67	61	58	66	61	57		65	61	57		64
10	73	64	58	54	72	63	58	54	63	58	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	333285
5°	314615
10°	306452
15°	299434
20°	278414
25°	248893
30°	190105
35°	109754
40°	42594
45°	17738
50°	3889
55°	612
60°	439
65°	259
70°	321
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 17738 cd/sqm

TEST NUMBER: P1260139

CATALOG NUMBER: P3AS13R609050DE010 E3D1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	134.9	10.6
10°-20°	367.4	28.9
20°-30°	460.2	36.2
30°-40°	257.3	20.2
40°-50°	48.9	3.8
50°-60°	2.5	0.2
60°-70°	0.6	0.0
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	962.6	75.7
0°-40°	1219.8	95.9
0°-60°	1271.2	99.9
0°-90°	1271.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1271.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1520	
5°	1429	135
15°	1319	367
25°	1029	460
35°	410	257
45°	57	49
55°	2	2
65°	0	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1260139

CATALOG NUMBER: P3AS13R609050DE010 E3D1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	1519.9
1°	1513.6
2°	1493.9
3°	1470.5
4°	1448.6
5°	1429.3
6°	1414.8
7°	1402.3
8°	1392.9
9°	1384.1
10°	1376.3
11°	1368.5
12°	1359.6
13°	1348.7
14°	1335.7
15°	1319.0
16°	1298.7
17°	1275.9
18°	1249.8
19°	1220.2
20°	1193.1
21°	1164.0
22°	1133.8
23°	1102.1
24°	1067.2
25°	1028.7
26°	983.4
27°	933.0
28°	876.2
29°	815.9
30°	750.8
31°	685.3
32°	617.6
32.5°	580.7
33°	547.4
34°	478.2
35°	410.0
36°	348.6
37°	283.6
37.5°	253.9
38°	224.8
39°	181.1
40°	148.8
42.5°	90.5
45°	57.2



TEST NUMBER: P1260139

CATALOG NUMBER: P3AS13R609050DE010 E3D1LI

CANDELA DISTRIBUTION (continued):

	0°
47.5°	31.7
50°	11.4
52.5°	2.6
55°	1.6
57.5°	1.0
60°	1.0
62.5°	0.5
65°	0.5
67.5°	0.5
70°	0.5
72.5°	0.5
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)