

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1260156

Luminaire Tested: P3AS13R609050DE010 E3DLP1H

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1260156  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-37)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS13R609050DE010 E3DLP1H  
Description: 3in Adjustable LED luminaire with, R60 optic, 5000K CCT AND, 90CRI , E3DLP1H TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 772.0 lumens  
Efficiency: N/A  
Efficacy: 52.9 lumens/watt  
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 14.6  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1260156

CATALOG NUMBER: P3AS13R609050DE010 E3DLP1H

### Luminous Intensity Polar Plot



TEST NUMBER: P1260156

CATALOG NUMBER: P3AS13R609050DE010 E3DLP1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 0   |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 0   |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 100 |
| 1   | 113 | 110 | 107 | 105 | 110 | 108 | 105 | 103 | 104 | 102 | 100 |  | 100 | 98  | 97  |  | 92  |
| 2   | 107 | 101 | 97  | 93  | 104 | 100 | 96  | 92  | 96  | 93  | 90  |  | 93  | 91  | 88  |  | 85  |
| 3   | 101 | 94  | 88  | 84  | 99  | 92  | 87  | 83  | 90  | 86  | 82  |  | 87  | 84  | 81  |  | 78  |
| 4   | 95  | 87  | 81  | 77  | 93  | 86  | 80  | 76  | 84  | 79  | 75  |  | 82  | 78  | 74  |  | 72  |
| 5   | 90  | 81  | 75  | 70  | 88  | 80  | 74  | 70  | 78  | 73  | 69  |  | 77  | 72  | 69  |  | 66  |
| 6   | 85  | 76  | 69  | 65  | 84  | 75  | 69  | 65  | 73  | 68  | 64  |  | 72  | 67  | 64  |  | 62  |
| 7   | 81  | 71  | 65  | 60  | 79  | 70  | 64  | 60  | 69  | 64  | 60  |  | 68  | 63  | 59  |  | 57  |
| 8   | 77  | 67  | 60  | 56  | 75  | 66  | 60  | 56  | 65  | 60  | 56  |  | 64  | 59  | 55  |  | 54  |
| 9   | 73  | 63  | 57  | 52  | 72  | 62  | 56  | 52  | 61  | 56  | 52  |  | 60  | 55  | 52  |  | 50  |
| 10  | 69  | 59  | 53  | 49  | 68  | 59  | 53  | 49  | 58  | 53  | 49  |  | 57  | 52  | 49  |  | 47  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 195642 |
| 5°  | 191261 |
| 10° | 179066 |
| 15° | 160637 |
| 20° | 138145 |
| 25° | 114224 |
| 30° | 90267  |
| 35° | 67030  |
| 40° | 46172  |
| 45° | 28964  |
| 50° | 15931  |
| 55° | 9328   |
| 60° | 8377   |
| 65° | 7160   |
| 70° | 6091   |
| 75° | 6270   |
| 80° | 5304   |
| 85° | 5284   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 28964 cd/sqm

TEST NUMBER: P1260156

CATALOG NUMBER: P3AS13R609050DE010 E3DLP1H

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 80.9   | 10.5      |
| 10°-20°   | 196.5  | 25.5      |
| 20°-30°   | 215.6  | 27.9      |
| 30°-40°   | 157.1  | 20.3      |
| 40°-50°   | 74.2   | 9.6       |
| 50°-60°   | 24.3   | 3.1       |
| 60°-70°   | 13.8   | 1.8       |
| 70°-80°   | 7.4    | 1.0       |
| 80°-90°   | 2.3    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 493.0  | 63.9      |
| 0°-40°    | 650.0  | 84.2      |
| 0°-60°    | 748.5  | 97.0      |
| 0°-90°    | 772.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 772.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 892 |      |
| 5°  | 869 | 81   |
| 15° | 708 | 197  |
| 25° | 472 | 216  |
| 35° | 250 | 157  |
| 45° | 93  | 74   |
| 55° | 24  | 24   |
| 65° | 14  | 14   |
| 75° | 7   | 7    |
| 85° | 2   | 2    |
| 90° | 0   |      |

TEST NUMBER: P1260156

CATALOG NUMBER: P3AS13R609050DE010 E3DLP1H

**CANDELA DISTRIBUTION (FULL):**

|       | 0°    |
|-------|-------|
| 0°    | 892.2 |
| 2.5°  | 886.9 |
| 5°    | 868.9 |
| 7.5°  | 841.3 |
| 10°   | 804.2 |
| 12.5° | 759.6 |
| 15°   | 707.6 |
| 17.5° | 651.4 |
| 20°   | 592.0 |
| 22.5° | 531.5 |
| 25°   | 472.1 |
| 27.5° | 412.7 |
| 30°   | 356.5 |
| 32.5° | 302.4 |
| 35°   | 250.4 |
| 37.5° | 203.7 |
| 40°   | 161.3 |
| 42.5° | 124.1 |
| 45°   | 93.4  |
| 47.5° | 67.9  |
| 50°   | 46.7  |
| 52.5° | 30.8  |
| 55°   | 24.4  |
| 57.5° | 21.2  |
| 60°   | 19.1  |
| 62.5° | 15.9  |
| 65°   | 13.8  |
| 67.5° | 11.7  |
| 70°   | 9.5   |
| 72.5° | 8.5   |
| 75°   | 7.4   |
| 77.5° | 5.3   |
| 80°   | 4.2   |
| 82.5° | 3.2   |
| 85°   | 2.1   |
| 87.5° | 1.1   |
| 90°   | 0.0   |

(END OF REPORT)