

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1260167

Luminaire Tested: P3AS13R659050DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1260167
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-16)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R659050DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R65 optic, 5000K CCT AND, 90CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1266.0 lumens
Efficiency: N/A
Efficacy: 86.7 lumens/watt
Spacing Criteria (0/90/45): 0.92 / 0.92 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1260167

CATALOG NUMBER: P3AS13R659050DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1260167

CATALOG NUMBER: P3AS13R659050DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	95	91	88	93	89	86		90	87	85		88
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84
5	93	85	79	75	92	84	79	75	82	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	69		76	72	69		75
7	84	75	70	65	83	75	69	65	73	69	65		72	68	65		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		68
9	77	67	61	58	76	67	61	57	66	61	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	339227
5°	314989
10°	304604
15°	293554
20°	271390
25°	247272
30°	191042
35°	110744
40°	43939
45°	18731
50°	4435
55°	612
60°	439
65°	259
70°	321
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 18731 cd/sqm

TEST NUMBER: P1260167

CATALOG NUMBER: P3AS13R659050DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	135.0	10.7
10°-20°	360.3	28.5
20°-30°	456.0	36.0
30°-40°	259.7	20.5
40°-50°	51.6	4.1
50°-60°	2.7	0.2
60°-70°	0.7	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	951.3	75.1
0°-40°	1211.0	95.7
0°-60°	1265.2	99.9
0°-90°	1266.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1266.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1547	
5°	1431	135
15°	1293	360
25°	1022	456
35°	414	260
45°	60	52
55°	2	3
65°	0	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1260167

CATALOG NUMBER: P3AS13R659050DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1547.0
1°	1535.6
2°	1510.6
3°	1481.5
4°	1452.8
5°	1431.0
6°	1414.9
7°	1401.8
8°	1390.4
9°	1378.9
10°	1368.0
11°	1356.1
12°	1343.6
13°	1328.5
14°	1312.3
15°	1293.1
16°	1270.2
17°	1245.2
18°	1218.2
19°	1189.5
20°	1163.0
21°	1135.9
22°	1111.5
23°	1086.0
24°	1056.3
25°	1022.0
26°	980.9
27°	931.4
28°	875.8
29°	816.4
30°	754.5
31°	686.4
32°	618.7
32.5°	583.8
33°	550.0
34°	481.3
35°	413.7
36°	351.2
37°	289.3
37.5°	257.6
38°	232.1
39°	187.8
40°	153.5
42.5°	94.7
45°	60.4



TEST NUMBER: P1260167

CATALOG NUMBER: P3AS13R659050DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	35.4
50°	13.0
52.5°	2.6
55°	1.6
57.5°	1.0
60°	1.0
62.5°	1.0
65°	0.5
67.5°	0.5
70°	0.5
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)