

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1260375

Luminaire Tested: P3AS17R359050DE010 E3DL1GPH

Issue Date: 1/30/2026

**Test Information**


Test Method: LM-79-2019  
Report Number: P1260375  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-19)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS17R359050DE010 E3DL1GPH  
Description: 3in Adjustable LED luminaire with, R35 optic, 5000K CCT AND, 90CRI , E3DL1GPH TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 724.1 lumens  
Efficiency: N/A  
Efficacy: 34.2 lumens/watt  
Spacing Criteria (0/90/45): 0.58 / 0.58 / 0.58  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 21.2  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1260375  
CATALOG NUMBER: P3AS17R359050DE010 E3DL1GPH

### Luminous Intensity Polar Plot





TEST NUMBER: P1260375  
 CATALOG NUMBER: P3AS17R359050DE010 E3DL1GPH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				20
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	114	112	109	107	112	109	107	106	105	104	102	102	100	99	98	97	96	95	95	95	95
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	93	91	90	90	90	90
3	105	99	95	91	103	98	94	90	95	92	89	93	90	88	91	88	86	85	85	85	85
4	100	94	89	85	99	93	88	85	91	87	84	89	85	83	87	84	82	80	80	80	80
5	96	89	84	80	95	88	83	80	86	82	79	85	81	78	83	80	78	76	76	76	76
6	92	85	80	76	91	84	79	76	83	78	75	81	77	75	80	77	74	73	73	73	73
7	89	81	76	72	88	80	75	72	79	75	71	78	74	71	77	73	71	70	70	70	70
8	85	77	72	69	84	77	72	68	76	71	68	75	71	68	74	70	68	66	66	66	66
9	82	74	69	66	81	74	69	65	73	68	65	72	68	65	71	67	65	64	64	64	64
10	79	71	66	63	78	71	66	63	70	66	63	69	65	62	69	65	62	61	61	61	61

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	365146
5°	350935
10°	305761
15°	234190
20°	156697
25°	94820
30°	54413
35°	30410
40°	16173
45°	8342
50°	3991
55°	3173
60°	3026
65°	2491
70°	2629
75°	2372
80°	2652
85°	1761

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 8342 cd/sqm



TEST NUMBER: P1260375  
 CATALOG NUMBER: P3AS17R359050DE010 E3DL1GPH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	145.1	20.0
10°-20°	281.1	38.8
20°-30°	184.0	25.4
30°-40°	74.7	10.3
40°-50°	22.4	3.1
50°-60°	7.6	1.1
60°-70°	5.1	0.7
70°-80°	3.0	0.4
80°-90°	1.0	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	610.2	84.3
0°-40°	684.9	94.6
0°-60°	714.9	98.7
0°-90°	724.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	724.1	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1665	
5°	1594	145
15°	1032	281
25°	392	184
35°	114	75
45°	27	22
55°	8	8
65°	5	5
75°	3	3
85°	1	1
90°	0	



TEST NUMBER: P1260375  
CATALOG NUMBER: P3AS17R359050DE010 E3DL1GPH

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	1665.2
1°	1662.5
2°	1654.9
3°	1639.8
4°	1621.8
5°	1594.3
6°	1559.9
7°	1521.3
8°	1477.9
9°	1428.3
10°	1373.2
11°	1311.9
12°	1247.9
13°	1176.3
14°	1108.1
15°	1031.6
17.5°	846.4
20°	671.5
22.5°	516.5
25°	391.9
27.5°	292.0
30°	214.9
32.5°	157.7
35°	113.6
37.5°	80.6
40°	56.5
42.5°	39.3
45°	26.9
47.5°	17.9
50°	11.7
52.5°	9.0
55°	8.3
57.5°	7.6
60°	6.9
62.5°	6.2
65°	4.8
67.5°	4.1
70°	4.1
72.5°	3.4
75°	2.8
77.5°	2.1
80°	2.1
82.5°	1.4
85°	0.7
87.5°	0.7



TEST NUMBER: P1260375  
CATALOG NUMBER: P3AS17R359050DE010 E3DL1GPH

CANDELA DISTRIBUTION (continued):

0°  
90° | 0.0

(END OF REPORT)