

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1260476

Luminaire Tested: P3AS17R509050DE010 E3DLP1MW

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1260476
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-29)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R509050DE010 E3DLP1MW
Description: 3in Adjustable LED luminaire with, R50 optic, 5000K CCT AND, 90CRI , E3DLP1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1038.0 lumens
Efficiency: N/A
Efficacy: 49.0 lumens/watt
Spacing Criteria (0/90/45): 0.75 / 0.75 / 0.77
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1260476

CATALOG NUMBER: P3AS17R509050DE010 E3DLP1MW

Luminous Intensity Polar Plot





TEST NUMBER: P1260476

CATALOG NUMBER: P3AS17R509050DE010 E3DLP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	106	103	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	95	89	85	99	93	88	85	91	87	83		88	85	82		86
4	96	88	82	78	94	87	82	78	85	80	77		83	79	76		81
5	91	83	76	72	90	82	76	72	80	75	71		78	74	70		77
6	87	77	71	67	85	77	71	67	75	70	66		74	69	66		72
7	82	73	67	62	81	72	66	62	71	66	62		70	65	61		68
8	78	69	63	58	77	68	62	58	67	62	58		66	61	58		65
9	75	65	59	55	74	64	59	55	63	58	55		63	58	54		62
10	71	61	56	52	70	61	55	52	60	55	51		59	55	51		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	301906
5°	293770
10°	270892
15°	238231
20°	199331
25°	158066
30°	115967
35°	79719
40°	50666
45°	28313
50°	15351
55°	12884
60°	11096
65°	10222
70°	8976
75°	8303
80°	7072
85°	7045

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 28313 cd/sqm

TEST NUMBER: P1260476

CATALOG NUMBER: P3AS17R509050DE010 E3DLP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	123.6	11.9
10°-20°	290.6	28.0
20°-30°	297.3	28.6
30°-40°	188.5	18.2
40°-50°	75.0	7.2
50°-60°	30.4	2.9
60°-70°	19.5	1.9
70°-80°	10.0	1.0
80°-90°	3.0	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	711.6	68.6
0°-40°	900.1	86.7
0°-60°	1005.5	96.9
0°-90°	1038.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1038.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1377	
5°	1335	124
15°	1049	291
25°	653	297
35°	298	189
45°	91	75
55°	34	30
65°	20	19
75°	10	10
85°	3	3
90°	0	

TEST NUMBER: P1260476

CATALOG NUMBER: P3AS17R509050DE010 E3DLP1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	1376.8
2.5°	1366.9
5°	1334.6
7.5°	1284.0
10°	1216.6
12.5°	1136.5
15°	1049.4
17.5°	953.9
20°	854.2
22.5°	754.4
25°	653.3
27.5°	552.1
30°	458.0
32.5°	373.7
35°	297.8
37.5°	233.2
40°	177.0
42.5°	130.7
45°	91.3
47.5°	61.8
50°	45.0
52.5°	37.9
55°	33.7
57.5°	29.5
60°	25.3
62.5°	22.5
65°	19.7
67.5°	16.9
70°	14.0
72.5°	11.2
75°	9.8
77.5°	7.0
80°	5.6
82.5°	4.2
85°	2.8
87.5°	1.4
90°	0.0

(END OF REPORT)