

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1261519

Luminaire Tested: P3AS02R359727DE010 E3DLD1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1261519
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-18)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R359727DE010 E3DLD1WH
Description: 3in Adjustable LED luminaire with, R35 optic, 2700K CCT AND, 97CRI , E3DLD1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 165.0 lumens
Efficiency: N/A
Efficacy: 45.8 lumens/watt
Spacing Criteria (0/90/45): 0.8 / 0.8 / 0.87
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1261519

CATALOG NUMBER: P3AS02R359727DE010 E3DLD1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1261519

CATALOG NUMBER: P3AS02R359727DE010 E3DLD1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	98	96		96
2	106	100	96	92	104	98	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	81	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	75	72		78
5	89	79	73	68	87	78	72	67	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	61		70	65	61		68
7	79	69	62	57	78	68	62	57	67	61	57		65	60	57		64
8	75	64	58	53	74	64	57	53	63	57	53		62	56	53		61
9	71	60	54	50	70	60	54	50	59	53	49		58	53	49		57
10	67	57	51	46	66	56	50	46	56	50	46		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	37694
5°	36892
10°	34557
15°	31010
20°	26976
25°	22985
30°	19269
35°	15339
40°	11078
45°	7008
50°	3821
55°	2638
60°	2500
65°	2335
70°	2244
75°	1864
80°	1768
85°	1510

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 7008 cd/sqm

TEST NUMBER: P1261519

CATALOG NUMBER: P3AS02R359727DE010 E3DLD1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	15.6	9.5
10°-20°	38.0	23.0
20°-30°	43.6	26.4
30°-40°	35.6	21.6
40°-50°	17.9	10.9
50°-60°	6.7	4.0
60°-70°	4.5	2.7
70°-80°	2.5	1.5
80°-90°	0.7	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	97.2	58.9
0°-40°	132.7	80.5
0°-60°	157.3	95.3
0°-90°	165.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	165.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	172	
5°	168	16
15°	137	38
25°	95	44
35°	57	36
45°	23	18
55°	7	7
65°	4	4
75°	2	2
85°	1	1
90°	0	

TEST NUMBER: P1261519

CATALOG NUMBER: P3AS02R359727DE010 E3DLD1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	171.9
1°	171.7
2°	171.3
3°	170.5
4°	169.2
5°	167.6
6°	165.6
7°	163.5
8°	160.9
9°	158.2
10°	155.2
11°	151.9
12°	148.4
13°	144.6
14°	140.5
15°	136.6
17.5°	126.2
20°	115.6
22.5°	104.8
25°	95.0
27.5°	85.4
30°	76.1
32.5°	66.7
35°	57.3
37.5°	47.9
40°	38.7
42.5°	30.2
45°	22.6
47.5°	16.3
50°	11.2
52.5°	8.2
55°	6.9
57.5°	6.3
60°	5.7
62.5°	5.1
65°	4.5
67.5°	3.9
70°	3.5
72.5°	2.9
75°	2.2
77.5°	1.8
80°	1.4
82.5°	1.0
85°	0.6
87.5°	0.4



TEST NUMBER: P1261519

CATALOG NUMBER: P3AS02R359727DE010 E3DLD1WH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)