

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1261630

Luminaire Tested: P3AS02R559727DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1261630
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-34)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R559727DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R55 optic, 2700K CCT AND, 97CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 85.0 lumens
Efficiency: N/A
Efficacy: 23.6 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.97
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1261630

CATALOG NUMBER: P3AS02R559727DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1261630

CATALOG NUMBER: P3AS02R559727DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	102	103	100	98		99	97	96		95
2	105	100	95	91	103	98	93	90	94	91	88		91	88	86		89
3	99	91	85	81	97	90	84	80	87	82	79		85	81	77		82
4	93	84	77	72	91	83	77	72	80	75	71		78	74	70		76
5	87	77	71	66	85	76	70	65	75	69	65		73	68	64		71
6	82	72	65	60	80	71	64	60	69	64	59		68	63	59		66
7	77	67	60	55	76	66	59	55	65	59	54		63	58	54		62
8	73	62	55	51	72	62	55	51	60	55	50		59	54	50		58
9	69	58	51	47	68	58	51	47	57	51	47		56	50	46		55
10	65	55	48	44	64	54	48	44	53	47	43		52	47	43		52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	15986
5°	15782
10°	15163
15°	14166
20°	12928
25°	11541
30°	10103
35°	8379
40°	6612
45°	4497
50°	2729
55°	1415
60°	1316
65°	1245
70°	1154
75°	1017
80°	1010
85°	755

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4497 cd/sqm

TEST NUMBER: P1261630

CATALOG NUMBER: P3AS02R559727DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	6.7	7.9
10°-20°	17.5	20.5
20°-30°	21.9	25.7
30°-40°	19.5	23.0
40°-50°	11.4	13.4
50°-60°	3.9	4.6
60°-70°	2.4	2.8
70°-80°	1.3	1.6
80°-90°	0.4	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	46.0	54.2
0°-40°	65.5	77.1
0°-60°	80.9	95.2
0°-90°	85.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	85.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	73	
5°	72	7
15°	62	17
25°	48	22
35°	31	20
45°	14	11
55°	4	4
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P1261630

CATALOG NUMBER: P3AS02R559727DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	72.9
2.5°	72.5
5°	71.7
7.5°	70.1
10°	68.1
12.5°	65.6
15°	62.4
17.5°	59.1
20°	55.4
22.5°	51.6
25°	47.7
27.5°	43.8
30°	39.9
32.5°	35.6
35°	31.3
37.5°	27.1
40°	23.1
42.5°	18.8
45°	14.5
47.5°	11.0
50°	8.0
52.5°	5.2
55°	3.7
57.5°	3.3
60°	3.0
62.5°	2.7
65°	2.4
67.5°	2.1
70°	1.8
72.5°	1.5
75°	1.2
77.5°	1.0
80°	0.8
82.5°	0.5
85°	0.3
87.5°	0.2
90°	0.0

(END OF REPORT)