

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1262158

Luminaire Tested: P3AS09R109727DE010 E3DLD1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1262158
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-2)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R109727DE010 E3DLD1H
Description: 3in Adjustable LED luminaire with, R10 optic, 2700K CCT AND, 97CRI , E3DLD1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 380.0 lumens
Efficiency: N/A
Efficacy: 30.4 lumens/watt
Spacing Criteria (0/90/45): 0.76 / 0.76 / 0.82
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 12.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1262158

CATALOG NUMBER: P3AS09R109727DE010 E3DLD1H

Luminous Intensity Polar Plot



TEST NUMBER: P1262158

CATALOG NUMBER: P3AS09R109727DE010 E3DLD1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	95	91	95	92	89		92	90	87		90
3	100	93	87	83	98	91	86	82	89	84	81		86	82	79		84
4	94	86	80	75	92	85	79	74	82	77	73		80	76	73		78
5	89	80	73	68	87	79	73	68	77	72	67		75	70	67		74
6	84	74	68	63	83	73	67	63	72	66	62		70	66	62		69
7	80	69	63	58	78	69	63	58	67	62	58		66	61	57		65
8	76	65	59	54	74	65	58	54	63	58	54		62	57	54		61
9	72	61	55	51	71	61	55	51	60	54	50		59	54	50		58
10	68	58	52	48	67	57	51	47	57	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	95848
5°	93242
10°	85213
15°	74643
20°	64032
25°	53471
30°	42791
35°	32096
40°	23301
45°	15226
50°	9518
55°	6423
60°	5701
65°	5241
70°	4937
75°	4490
80°	4293
85°	3522

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15226 cd/sqm

TEST NUMBER: P1262158

CATALOG NUMBER: P3AS09R109727DE010 E3DLD1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	39.1	10.3
10°-20°	91.6	24.1
20°-30°	101.0	26.6
30°-40°	75.6	19.9
40°-50°	39.2	10.3
50°-60°	16.2	4.3
60°-70°	10.1	2.7
70°-80°	5.7	1.5
80°-90°	1.6	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	231.7	61.0
0°-40°	307.3	80.9
0°-60°	362.7	95.4
0°-90°	380.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	380.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	437	
5°	424	39
15°	329	92
25°	221	101
35°	120	76
45°	49	39
55°	17	16
65°	10	10
75°	5	6
85°	1	2
90°	0	

TEST NUMBER: P1262158

CATALOG NUMBER: P3AS09R109727DE010 E3DLD1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	437.1
1°	437.6
2°	436.1
3°	433.3
4°	428.9
5°	423.6
6°	416.9
7°	409.7
8°	401.0
9°	391.9
10°	382.7
12.5°	356.2
15°	328.8
17.5°	301.4
20°	274.4
22.5°	247.0
25°	221.0
27.5°	195.0
30°	169.0
32.5°	143.5
35°	119.9
37.5°	99.6
40°	81.4
42.5°	64.5
45°	49.1
47.5°	37.1
50°	27.9
52.5°	20.7
55°	16.8
57.5°	14.9
60°	13.0
62.5°	11.6
65°	10.1
67.5°	8.7
70°	7.7
72.5°	6.3
75°	5.3
77.5°	4.3
80°	3.4
82.5°	2.4
85°	1.4
87.5°	0.5
90°	0.0

(END OF REPORT)