

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1262218

Luminaire Tested: P3AS09R209727DE010 E3DLD1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1262218
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-6)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R209727DE010 E3DLD1H
Description: 3in Adjustable LED luminaire with, R20 optic, 2700K CCT AND, 97CRI , E3DLD1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 482.0 lumens
Efficiency: N/A
Efficacy: 43.4 lumens/watt
Spacing Criteria (0/90/45): 0.76 / 0.76 / 0.83
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1262218

CATALOG NUMBER: P3AS09R209727DE010 E3DLD1H

Luminous Intensity Polar Plot



TEST NUMBER: P1262218

CATALOG NUMBER: P3AS09R209727DE010 E3DLD1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		90
3	100	93	87	82	98	91	86	82	88	84	80		86	82	79		84
4	94	86	79	75	92	85	79	74	82	77	73		80	76	72		78
5	89	80	73	68	87	79	73	68	77	71	67		75	70	67		73
6	84	74	68	63	82	73	67	63	72	66	62		70	65	62		69
7	80	69	63	58	78	69	62	58	67	62	58		66	61	57		65
8	75	65	59	54	74	64	58	54	63	58	54		62	57	53		61
9	72	61	55	50	70	61	55	50	60	54	50		59	54	50		58
10	68	58	51	47	67	57	51	47	56	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	119223
5°	116046
10°	106745
15°	93962
20°	80577
25°	67697
30°	54717
35°	41626
40°	29627
45°	19568
50°	12110
55°	7952
60°	7236
65°	6693
70°	6283
75°	5676
80°	5430
85°	4529

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 19568 cd/sqm

TEST NUMBER: P1262218

CATALOG NUMBER: P3AS09R209727DE010 E3DLD1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	48.8	10.1
10°-20°	115.2	23.9
20°-30°	127.9	26.5
30°-40°	97.6	20.2
40°-50°	50.0	10.4
50°-60°	20.5	4.3
60°-70°	12.8	2.7
70°-80°	7.2	1.5
80°-90°	2.1	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	291.9	60.6
0°-40°	389.4	80.8
0°-60°	459.9	95.4
0°-90°	482.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	482.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	544	
5°	527	49
15°	414	115
25°	280	128
35°	156	98
45°	63	50
55°	21	21
65°	13	13
75°	7	7
85°	2	2
90°	0	

TEST NUMBER: P1262218

CATALOG NUMBER: P3AS09R209727DE010 E3DLD1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	543.7
1°	544.3
2°	541.9
3°	538.8
4°	533.9
5°	527.2
6°	519.2
7°	510.6
8°	501.5
9°	490.4
10°	479.4
12.5°	447.6
15°	413.9
17.5°	379.6
20°	345.3
22.5°	311.0
25°	279.8
27.5°	248.6
30°	216.1
32.5°	185.5
35°	155.5
37.5°	129.2
40°	103.5
42.5°	81.4
45°	63.1
47.5°	47.8
50°	35.5
52.5°	26.3
55°	20.8
57.5°	19.0
60°	16.5
62.5°	14.7
65°	12.9
67.5°	11.0
70°	9.8
72.5°	8.0
75°	6.7
77.5°	5.5
80°	4.3
82.5°	3.1
85°	1.8
87.5°	0.6
90°	0.0

(END OF REPORT)