

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1262325

Luminaire Tested: P3AS09R409727DE010 E3D1H

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1262325
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-12)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R409727DE010 E3D1H
Description: 3in Adjustable LED luminaire with, R40 optic, 2700K CCT AND, 97CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 858.0 lumens
Efficiency: N/A
Efficacy: 77.3 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.6
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1262325

CATALOG NUMBER: P3AS09R409727DE010 E3D1H

Luminous Intensity Polar Plot



TEST NUMBER: P1262325

CATALOG NUMBER: P3AS09R409727DE010 E3D1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	109	112	110	109	107	106	105	104		103	102	101		99
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		96
3	107	102	98	95	105	100	97	94	98	95	93		96	93	91		93
4	103	97	93	90	101	96	92	89	94	91	88		92	89	87		90
5	99	93	89	85	98	92	88	85	91	87	84		89	86	84		88
6	96	89	85	81	95	89	84	81	87	83	81		86	83	80		85
7	93	86	81	78	92	85	81	78	84	80	77		83	80	77		82
8	90	83	78	75	89	82	78	75	81	77	75		80	77	74		79
9	87	80	75	72	86	79	75	72	78	75	72		78	74	72		77
10	84	77	72	70	83	77	72	69	76	72	69		75	72	69		74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	437333
5°	434183
10°	422816
15°	377687
20°	250435
25°	93828
30°	25092
35°	9798
40°	3521
45°	1675
50°	512
55°	229
60°	132
65°	156
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1675 cd/sqm

TEST NUMBER: P1262325

CATALOG NUMBER: P3AS09R409727DE010 E3D1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	186.1	21.7
10°-20°	440.8	51.4
20°-30°	199.9	23.3
30°-40°	25.9	3.0
40°-50°	4.5	0.5
50°-60°	0.5	0.1
60°-70°	0.2	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	826.9	96.4
0°-40°	852.8	99.4
0°-60°	857.8	100.0
0°-90°	858.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	858.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1994	
5°	1972	186
15°	1664	441
25°	388	200
35°	37	26
45°	5	4
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1262325

CATALOG NUMBER: P3AS09R409727DE010 E3D1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1994.4
1°	1993.2
2°	1990.2
3°	1985.7
4°	1980.0
5°	1972.5
6°	1963.8
7°	1953.0
8°	1939.8
9°	1921.8
10°	1898.9
11°	1872.2
12°	1836.4
13°	1792.3
14°	1734.6
15°	1663.7
16°	1573.3
17°	1470.3
18°	1346.5
19°	1215.9
20°	1073.2
21°	930.5
22°	790.0
23°	650.0
24°	512.4
25°	387.8
26°	287.2
27°	210.3
28°	158.0
29°	122.9
30°	99.1
31°	82.0
32°	68.5
32.5°	62.5
33°	56.5
34°	46.0
35°	36.6
36°	28.8
37°	22.8
37.5°	20.4
38°	18.0
39°	15.0
40°	12.3
42.5°	8.1
45°	5.4

TEST NUMBER: P1262325

CATALOG NUMBER: P3AS09R409727DE010 E3D1H

CANDELA DISTRIBUTION (continued):

	0°
47.5°	3.3
50°	1.5
52.5°	0.6
55°	0.6
57.5°	0.3
60°	0.3
62.5°	0.3
65°	0.3
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)