

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1262448

Luminaire Tested: P3AS09R609727DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1262448
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-38)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R609727DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R60 optic, 2700K CCT AND, 97CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 247.9 lumens
Efficiency: N/A
Efficacy: 22.3 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1262448

CATALOG NUMBER: P3AS09R609727DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1262448

CATALOG NUMBER: P3AS09R609727DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	98	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	91	82	76	71	80	75	71		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	44032
5°	43539
10°	42017
15°	39705
20°	36590
25°	33147
30°	29422
35°	25136
40°	19980
45°	14110
50°	8426
55°	4244
60°	4079
65°	3736
70°	3462
75°	3304
80°	3031
85°	2264

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 14110 cd/sqm

TEST NUMBER: P1262448

CATALOG NUMBER: P3AS09R609727DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	18.6	7.5
10°-20°	48.9	19.7
20°-30°	62.8	25.3
30°-40°	58.2	23.5
40°-50°	35.4	14.3
50°-60°	11.8	4.7
60°-70°	7.2	2.9
70°-80°	4.0	1.6
80°-90°	1.1	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	130.2	52.5
0°-40°	188.4	76.0
0°-60°	235.6	95.0
0°-90°	247.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	247.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	201	
5°	198	19
15°	175	49
25°	137	63
35°	94	58
45°	46	35
55°	11	12
65°	7	7
75°	4	4
85°	1	1
90°	0	

TEST NUMBER: P1262448

CATALOG NUMBER: P3AS09R609727DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	200.8
2.5°	199.9
5°	197.8
7.5°	193.8
10°	188.7
12.5°	182.4
15°	174.9
17.5°	166.1
20°	156.8
22.5°	146.9
25°	137.0
27.5°	126.7
30°	116.2
32.5°	105.6
35°	93.9
37.5°	81.6
40°	69.8
42.5°	57.5
45°	45.5
47.5°	35.2
50°	24.7
52.5°	14.7
55°	11.1
57.5°	10.2
60°	9.3
62.5°	8.1
65°	7.2
67.5°	6.3
70°	5.4
72.5°	4.5
75°	3.9
77.5°	3.0
80°	2.4
82.5°	1.5
85°	0.9
87.5°	0.6
90°	0.0

(END OF REPORT)