

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1262478

Luminaire Tested: P3AS09R659727DE010 E3DLD1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1262478
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-42)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R659727DE010 E3DLD1H
Description: 3in Adjustable LED luminaire with, R65 optic, 2700K CCT AND, 97CRI , E3DLD1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 483.0 lumens
Efficiency: N/A
Efficacy: 43.5 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1262478

CATALOG NUMBER: P3AS09R659727DE010 E3DLD1H

Luminous Intensity Polar Plot



TEST NUMBER: P1262478

CATALOG NUMBER: P3AS09R659727DE010 E3DLD1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	85958
5°	84790
10°	81940
15°	77276
20°	71290
25°	64697
30°	57325
35°	48774
40°	38816
45°	27383
50°	15897
55°	8678
60°	8070
65°	7316
70°	6668
75°	6270
80°	5430
85°	4529

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 27383 cd/sqm

TEST NUMBER: P1262478

CATALOG NUMBER: P3AS09R659727DE010 E3DLD1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	36.2	7.5
10°-20°	95.2	19.7
20°-30°	122.4	25.3
30°-40°	113.2	23.4
40°-50°	68.4	14.2
50°-60°	23.3	4.8
60°-70°	14.0	2.9
70°-80°	7.9	1.6
80°-90°	2.2	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	253.9	52.6
0°-40°	367.1	76.0
0°-60°	458.8	95.0
0°-90°	483.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	483.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	392	
5°	385	36
15°	340	95
25°	267	122
35°	182	113
45°	88	68
55°	23	23
65°	14	14
75°	7	8
85°	2	2
90°	0	

TEST NUMBER: P1262478

CATALOG NUMBER: P3AS09R659727DE010 E3DLD1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	392.0
2.5°	390.1
5°	385.2
7.5°	377.9
10°	368.0
12.5°	355.8
15°	340.4
17.5°	323.9
20°	305.5
22.5°	286.5
25°	267.4
27.5°	247.2
30°	226.4
32.5°	205.5
35°	182.2
37.5°	159.5
40°	135.6
42.5°	111.6
45°	88.3
47.5°	66.9
50°	46.6
52.5°	29.4
55°	22.7
57.5°	20.2
60°	18.4
62.5°	15.9
65°	14.1
67.5°	12.3
70°	10.4
72.5°	9.2
75°	7.4
77.5°	6.1
80°	4.3
82.5°	3.1
85°	1.8
87.5°	1.2
90°	0.0

(END OF REPORT)