

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1262501

Luminaire Tested: P3AS09R709727DE010 E3DL1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1262501
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-47)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R709727DE010 E3DL1H
Description: 3in Adjustable LED luminaire with, R70 optic, 2700K CCT AND, 97CRI , E3DL1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 617.0 lumens
Efficiency: N/A
Efficacy: 55.6 lumens/watt
Spacing Criteria (0/90/45): 0.97 / 0.97 / 0.98
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1262501

CATALOG NUMBER: P3AS09R709727DE010 E3DL1H

Luminous Intensity Polar Plot



TEST NUMBER: P1262501

CATALOG NUMBER: P3AS09R709727DE010 E3DL1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	104	110	107	105	103	103	101	100		100	98	97		96
2	106	101	96	93	104	99	95	92	96	93	90		93	90	88		90
3	100	93	88	83	98	92	87	82	89	85	81		86	83	80		84
4	94	86	80	75	93	85	79	75	83	78	74		81	76	73		79
5	89	80	73	69	87	79	73	68	77	72	68		75	71	67		74
6	84	74	68	63	82	73	67	63	72	66	62		70	65	62		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	53	74	64	58	53	63	57	53		62	57	53		61
9	71	60	54	50	70	60	54	50	59	53	49		58	53	49		57
10	67	57	50	46	66	56	50	46	55	50	46		55	49	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	119442
5°	118005
10°	114605
15°	109740
20°	102816
25°	93392
30°	80671
35°	64300
40°	46831
45°	30794
50°	14430
55°	4435
60°	4298
65°	4151
70°	3911
75°	4151
80°	3915
85°	3019

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 30794 cd/sqm

TEST NUMBER: P1262501

CATALOG NUMBER: P3AS09R709727DE010 E3DL1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	50.5	8.2
10°-20°	135.3	21.9
20°-30°	175.8	28.5
30°-40°	149.2	24.2
40°-50°	76.9	12.5
50°-60°	14.8	2.4
60°-70°	8.1	1.3
70°-80°	4.9	0.8
80°-90°	1.4	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	361.6	58.6
0°-40°	510.8	82.8
0°-60°	602.6	97.7
0°-90°	617.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	617.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	545	
5°	536	50
15°	483	135
25°	386	176
35°	240	149
45°	99	77
55°	12	15
65°	8	8
75°	5	5
85°	1	1
90°	0	

TEST NUMBER: P1262501

CATALOG NUMBER: P3AS09R709727DE010 E3DL1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	544.7
2.5°	542.9
5°	536.1
7.5°	526.3
10°	514.7
12.5°	500.0
15°	483.4
17.5°	463.2
20°	440.6
22.5°	414.8
25°	386.0
27.5°	353.5
30°	318.6
32.5°	280.0
35°	240.2
37.5°	201.0
40°	163.6
42.5°	128.7
45°	99.3
47.5°	72.9
50°	42.3
52.5°	18.4
55°	11.6
57.5°	11.0
60°	9.8
62.5°	9.2
65°	8.0
67.5°	7.4
70°	6.1
72.5°	5.5
75°	4.9
77.5°	3.7
80°	3.1
82.5°	1.8
85°	1.2
87.5°	0.6
90°	0.0

(END OF REPORT)