

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1263504

Luminaire Tested: P3AS20R459727D010 E3DLP1MW

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1263504
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-25)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R459727D010 E3DLP1MW
Description: 3in Adjustable LED luminaire with, R45 optic, 2700K CCT AND, 97CRI , E3DLP1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1021.0 lumens
Efficiency: N/A
Efficacy: 35.5 lumens/watt
Spacing Criteria (0/90/45): 0.73 / 0.73 / 0.76
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1263504

CATALOG NUMBER: P3AS20R459727D010 E3DLP1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1263504

CATALOG NUMBER: P3AS20R459727D010 E3DLP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	106	103	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	102	95	90	85	100	93	89	85	91	87	83		88	85	82		86
4	96	88	83	78	94	87	82	78	85	81	77		83	79	76		81
5	91	83	77	72	90	82	76	72	80	75	71		78	74	71		77
6	87	78	72	67	85	77	71	67	75	70	66		74	69	66		73
7	83	73	67	63	81	72	67	63	71	66	62		70	65	62		69
8	79	69	63	59	77	68	63	59	67	62	58		66	62	58		65
9	75	65	59	55	74	65	59	55	64	59	55		63	58	55		62
10	72	62	56	52	71	61	56	52	61	55	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	304120
5°	297182
10°	274143
15°	238390
20°	195830
25°	152380
30°	112524
35°	79183
40°	49435
45°	26762
50°	14498
55°	12425
60°	11183
65°	9547
70°	8142
75°	8388
80°	7198
85°	7045

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 26762 cd/sqm

TEST NUMBER: P1263504

CATALOG NUMBER: P3AS20R459727D010 E3DLP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	125.0	12.2
10°-20°	290.3	28.4
20°-30°	288.2	28.2
30°-40°	185.6	18.2
40°-50°	71.5	7.0
50°-60°	29.1	2.8
60°-70°	18.4	1.8
70°-80°	9.9	1.0
80°-90°	3.1	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	703.5	68.9
0°-40°	889.1	87.1
0°-60°	989.7	96.9
0°-90°	1021.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1021.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1387	
5°	1350	125
15°	1050	290
25°	630	288
35°	296	186
45°	86	71
55°	32	29
65°	18	18
75°	10	10
85°	3	3
90°	0	

TEST NUMBER: P1263504

CATALOG NUMBER: P3AS20R459727D010 E3DLP1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	1386.9
2.5°	1379.8
5°	1350.1
7.5°	1299.1
10°	1231.2
12.5°	1146.3
15°	1050.1
17.5°	945.3
20°	839.2
22.5°	731.6
25°	629.8
27.5°	533.5
30°	444.4
32.5°	366.5
35°	295.8
37.5°	232.1
40°	172.7
42.5°	124.5
45°	86.3
47.5°	58.0
50°	42.5
52.5°	35.4
55°	32.5
57.5°	28.3
60°	25.5
62.5°	21.2
65°	18.4
67.5°	15.6
70°	12.7
72.5°	11.3
75°	9.9
77.5°	7.1
80°	5.7
82.5°	4.2
85°	2.8
87.5°	1.4
90°	0.0

(END OF REPORT)