

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1264060

Luminaire Tested: P3AS02R659730DE010 E3D1WMH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1264060
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-16)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R659730DE010 E3D1WMH
Description: 3in Adjustable LED luminaire with, R65 optic, 3000K CCT AND, 97CRI , E3D1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 261.0 lumens
Efficiency: N/A
Efficacy: 72.5 lumens/watt
Spacing Criteria (0/90/45): 0.92 / 0.92 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1264060

CATALOG NUMBER: P3AS02R659730DE010 E3D1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1264060

CATALOG NUMBER: P3AS02R659730DE010 E3D1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	95	91	88	93	89	86		90	87	85		88
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84
5	93	85	79	75	92	84	79	75	82	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	69		76	72	69		75
7	84	75	70	65	83	75	69	65	73	69	65		72	68	65		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		68
9	77	67	61	58	76	67	61	57	66	61	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	69929
5°	64935
10°	62791
15°	60522
20°	55958
25°	50979
30°	39398
35°	22834
40°	9046
45°	3845
50°	921
55°	115
60°	88
65°	52
70°	64
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3845 cd/sqm

TEST NUMBER: P1264060

CATALOG NUMBER: P3AS02R659730DE010 E3D1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	27.8	10.7
10°-20°	74.3	28.5
20°-30°	94.0	36.0
30°-40°	53.5	20.5
40°-50°	10.6	4.1
50°-60°	0.5	0.2
60°-70°	0.1	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	196.1	75.2
0°-40°	249.6	95.7
0°-60°	260.8	99.9
0°-90°	261.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	261.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	319	
5°	295	28
15°	267	74
25°	211	94
35°	85	54
45°	12	11
55°	0	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1264060

CATALOG NUMBER: P3AS02R659730DE010 E3D1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	318.9
1°	316.6
2°	311.4
3°	305.4
4°	299.5
5°	295.0
6°	291.7
7°	289.0
8°	286.6
9°	284.3
10°	282.0
11°	279.6
12°	277.0
13°	273.9
14°	270.6
15°	266.6
16°	261.9
17°	256.7
18°	251.1
19°	245.2
20°	239.8
21°	234.2
22°	229.1
23°	223.9
24°	217.8
25°	210.7
26°	202.2
27°	192.0
28°	180.5
29°	168.3
30°	155.6
31°	141.5
32°	127.6
32.5°	120.4
33°	113.4
34°	99.2
35°	85.3
36°	72.4
37°	59.6
37.5°	53.1
38°	47.8
39°	38.7
40°	31.6
42.5°	19.5
45°	12.4



TEST NUMBER: P1264060

CATALOG NUMBER: P3AS02R659730DE010 E3D1WMH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	7.3
50°	2.7
52.5°	0.5
55°	0.3
57.5°	0.2
60°	0.2
62.5°	0.2
65°	0.1
67.5°	0.1
70°	0.1
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)