

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1264501

Luminaire Tested: P3AS05R709730DE010 E3DL1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1264501
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-47)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R709730DE010 E3DL1GPH
Description: 3in Adjustable LED luminaire with, R70 optic, 3000K CCT AND, 97CRI , E3DL1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 222.0 lumens
Efficiency: N/A
Efficacy: 30.8 lumens/watt
Spacing Criteria (0/90/45): 0.97 / 0.97 / 0.98
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1264501

CATALOG NUMBER: P3AS05R709730DE010 E3DL1GPH

Luminous Intensity Polar Plot





TEST NUMBER: P1264501

CATALOG NUMBER: P3AS05R709730DE010 E3DL1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	104	110	107	105	103	103	101	100		100	98	97		96
2	106	101	96	93	104	99	95	92	96	93	90		93	90	88		90
3	100	93	88	83	98	92	87	82	89	85	81		86	83	80		84
4	94	86	80	75	93	85	79	75	83	78	74		81	76	73		79
5	89	80	73	69	87	79	73	68	77	72	68		75	71	67		74
6	84	74	68	63	82	73	67	63	72	66	62		70	65	62		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	53	74	64	58	53	63	57	53		62	57	53		61
9	71	60	54	50	70	60	54	50	59	53	49		58	53	49		57
10	67	57	50	46	66	56	50	46	55	50	46		55	49	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	42979
5°	42461
10°	41237
15°	39478
20°	36987
25°	33607
30°	29017
35°	23129
40°	16860
45°	11071
50°	5185
55°	1606
60°	1535
65°	1505
70°	1410
75°	1525
80°	1389
85°	1006

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 11071 cd/sqm

TEST NUMBER: P1264501

CATALOG NUMBER: P3AS05R709730DE010 E3DL1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	18.2	8.2
10°-20°	48.7	21.9
20°-30°	63.3	28.5
30°-40°	53.7	24.2
40°-50°	27.7	12.5
50°-60°	5.3	2.4
60°-70°	2.9	1.3
70°-80°	1.8	0.8
80°-90°	0.5	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	130.1	58.6
0°-40°	183.8	82.8
0°-60°	216.8	97.7
0°-90°	222.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	222.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	196	
5°	193	18
15°	174	49
25°	139	63
35°	86	54
45°	36	28
55°	4	5
65°	3	3
75°	2	2
85°	0	1
90°	0	

TEST NUMBER: P1264501

CATALOG NUMBER: P3AS05R709730DE010 E3DL1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	196.0
2.5°	195.3
5°	192.9
7.5°	189.4
10°	185.2
12.5°	179.9
15°	173.9
17.5°	166.7
20°	158.5
22.5°	149.3
25°	138.9
27.5°	127.2
30°	114.6
32.5°	100.8
35°	86.4
37.5°	72.3
40°	58.9
42.5°	46.3
45°	35.7
47.5°	26.2
50°	15.2
52.5°	6.6
55°	4.2
57.5°	4.0
60°	3.5
62.5°	3.3
65°	2.9
67.5°	2.6
70°	2.2
72.5°	2.0
75°	1.8
77.5°	1.3
80°	1.1
82.5°	0.7
85°	0.4
87.5°	0.2
90°	0.0

(END OF REPORT)