

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1264565

Luminaire Tested: P3AS09R159730DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1264565
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-2)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R159730DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R15 optic, 3000K CCT AND, 97CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 254.0 lumens
Efficiency: N/A
Efficacy: 22.9 lumens/watt
Spacing Criteria (0/90/45): 0.75 / 0.75 / 0.82
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1264565

CATALOG NUMBER: P3AS09R159730DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1264565

CATALOG NUMBER: P3AS09R159730DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	95	91	95	92	89		92	90	87		90
3	100	93	87	83	98	91	86	82	89	84	81		86	82	79		84
4	94	86	80	75	92	85	79	74	82	77	73		80	76	73		78
5	89	80	73	68	87	79	73	68	77	72	67		75	70	67		74
6	84	74	68	63	83	73	67	63	72	66	62		70	66	62		69
7	80	69	63	58	78	69	63	58	67	62	58		66	61	57		65
8	76	65	59	54	74	65	58	54	63	58	54		62	57	54		61
9	72	61	55	51	71	61	55	51	60	54	50		59	54	50		58
10	68	58	52	48	67	57	51	47	57	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	64074
5°	62338
10°	56957
15°	49898
20°	42797
25°	35736
30°	28587
35°	21442
40°	15572
45°	10172
50°	6379
55°	4320
60°	3815
65°	3528
70°	3270
75°	2965
80°	2904
85°	2516

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10172 cd/sqm

TEST NUMBER: P1264565

CATALOG NUMBER: P3AS09R159730DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	26.1	10.3
10°-20°	61.2	24.1
20°-30°	67.5	26.6
30°-40°	50.5	19.9
40°-50°	26.2	10.3
50°-60°	10.9	4.3
60°-70°	6.7	2.6
70°-80°	3.8	1.5
80°-90°	1.1	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	154.8	61.0
0°-40°	205.3	80.8
0°-60°	242.4	95.4
0°-90°	254.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	254.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	292	
5°	283	26
15°	220	61
25°	148	67
35°	80	51
45°	33	26
55°	11	11
65°	7	7
75°	4	4
85°	1	1
90°	0	

TEST NUMBER: P1264565

CATALOG NUMBER: P3AS09R159730DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	292.2
1°	292.5
2°	291.5
3°	289.6
4°	286.7
5°	283.2
6°	278.7
7°	273.8
8°	268.0
9°	261.9
10°	255.8
12.5°	238.1
15°	219.8
17.5°	201.4
20°	183.4
22.5°	165.1
25°	147.7
27.5°	130.3
30°	112.9
32.5°	95.9
35°	80.1
37.5°	66.6
40°	54.4
42.5°	43.1
45°	32.8
47.5°	24.8
50°	18.7
52.5°	13.8
55°	11.3
57.5°	10.0
60°	8.7
62.5°	7.7
65°	6.8
67.5°	5.8
70°	5.1
72.5°	4.2
75°	3.5
77.5°	2.9
80°	2.3
82.5°	1.6
85°	1.0
87.5°	0.3
90°	0.0

(END OF REPORT)