

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1264877

Luminaire Tested: P3AS09R709730DE010 E3D1WH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1264877
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-17)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R709730DE010 E3D1WH
Description: 3in Adjustable LED luminaire with, R70 optic, 3000K CCT AND, 97CRI , E3D1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 782.9 lumens
Efficiency: N/A
Efficacy: 70.5 lumens/watt
Spacing Criteria (0/90/45): 1.02 / 1.02 / 1.06
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1264877

CATALOG NUMBER: P3AS09R709730DE010 E3D1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1264877

CATALOG NUMBER: P3AS09R709730DE010 E3D1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	81		86
4	95	87	81	77	94	86	81	77	84	79	76		82	78	75		80
5	90	81	75	70	88	80	74	70	78	73	69		77	72	69		75
6	85	75	69	64	83	75	69	64	73	68	64		72	67	63		70
7	80	70	64	59	79	70	63	59	68	63	59		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	61	55	51	71	61	55	51	60	54	50		59	54	50		58
10	68	58	51	47	67	57	51	47	56	51	47		55	50	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	152247
5°	143561
10°	136114
15°	133667
20°	128858
25°	121459
30°	120601
35°	105016
40°	67927
45°	32127
50°	4503
55°	382
60°	263
65°	311
70°	192
75°	254
80°	379
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 32127 cd/sqm

TEST NUMBER: P1264877

CATALOG NUMBER: P3AS09R709730DE010 E3D1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	60.9	7.8
10°-20°	165.4	21.1
20°-30°	233.9	29.9
30°-40°	235.1	30.0
40°-50°	84.5	10.8
50°-60°	2.3	0.3
60°-70°	0.5	0.1
70°-80°	0.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	460.2	58.8
0°-40°	695.3	88.8
0°-60°	782.1	99.9
0°-90°	782.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	782.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	694	
5°	652	61
15°	589	165
25°	502	234
35°	392	235
45°	104	85
55°	1	2
65°	1	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1264877

CATALOG NUMBER: P3AS09R709730DE010 E3D1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	694.3
1°	692.4
2°	686.3
3°	676.6
4°	664.4
5°	652.2
6°	640.6
7°	631.6
8°	623.6
9°	617.1
10°	611.3
11°	606.5
12°	602.0
13°	597.5
14°	593.3
15°	588.8
16°	583.4
17°	577.6
18°	570.5
19°	561.8
20°	552.2
21°	541.6
22°	530.9
23°	520.7
24°	510.7
25°	502.0
26°	495.9
27°	491.1
28°	487.2
29°	482.7
30°	476.3
31°	466.9
32°	453.8
32.5°	446.4
33°	436.4
34°	416.8
35°	392.3
36°	365.3
37°	334.8
37.5°	320.6
38°	301.3
39°	266.9
40°	237.3
42.5°	164.3
45°	103.6



TEST NUMBER: P1264877

CATALOG NUMBER: P3AS09R709730DE010 E3D1WH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	55.6
50°	13.2
52.5°	1.6
55°	1.0
57.5°	1.0
60°	0.6
62.5°	0.6
65°	0.6
67.5°	0.3
70°	0.3
72.5°	0.3
75°	0.3
77.5°	0.3
80°	0.3
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)