

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1264888

Luminaire Tested: P3AS09R709730DE010 E3DLP1MW

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1264888  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-45)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS09R709730DE010 E3DLP1MW  
Description: 3in Adjustable LED luminaire with, R70 optic, 3000K CCT AND, 97CRI , E3DLP1MW TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 472.0 lumens  
Efficiency: N/A  
Efficacy: 42.5 lumens/watt  
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.87  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 11.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1264888

CATALOG NUMBER: P3AS09R709730DE010 E3DLP1MW

### Luminous Intensity Polar Plot



TEST NUMBER: P1264888

CATALOG NUMBER: P3AS09R709730DE010 E3DLP1MW

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 107 | 104 | 110 | 107 | 105 | 103 | 103 | 101 | 100 |  | 100 | 98  | 97  |  | 96  |
| 2   | 106 | 101 | 97  | 93  | 104 | 99  | 95  | 92  | 96  | 93  | 90  |  | 93  | 90  | 88  |  | 90  |
| 3   | 100 | 93  | 88  | 83  | 98  | 92  | 87  | 83  | 89  | 85  | 81  |  | 87  | 83  | 80  |  | 84  |
| 4   | 95  | 86  | 80  | 76  | 93  | 85  | 80  | 75  | 83  | 78  | 74  |  | 81  | 77  | 73  |  | 79  |
| 5   | 89  | 80  | 74  | 69  | 88  | 79  | 73  | 69  | 78  | 72  | 68  |  | 76  | 71  | 68  |  | 74  |
| 6   | 85  | 75  | 68  | 64  | 83  | 74  | 68  | 64  | 73  | 67  | 63  |  | 71  | 66  | 63  |  | 70  |
| 7   | 80  | 70  | 64  | 59  | 79  | 69  | 63  | 59  | 68  | 62  | 58  |  | 67  | 62  | 58  |  | 66  |
| 8   | 76  | 66  | 59  | 55  | 75  | 65  | 59  | 55  | 64  | 58  | 54  |  | 63  | 58  | 54  |  | 62  |
| 9   | 72  | 62  | 55  | 51  | 71  | 61  | 55  | 51  | 60  | 55  | 51  |  | 59  | 54  | 51  |  | 58  |
| 10  | 69  | 58  | 52  | 48  | 67  | 58  | 52  | 48  | 57  | 51  | 48  |  | 56  | 51  | 48  |  | 55  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 110715 |
| 5°  | 108672 |
| 10° | 102470 |
| 15° | 93008  |
| 20° | 81347  |
| 25° | 68617  |
| 30° | 56186  |
| 35° | 43580  |
| 40° | 31201  |
| 45° | 19754  |
| 50° | 9859   |
| 55° | 6040   |
| 60° | 5175   |
| 65° | 4774   |
| 70° | 4231   |
| 75° | 3897   |
| 80° | 3283   |
| 85° | 3271   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 19754 cd/sqm

TEST NUMBER: P1264888

CATALOG NUMBER: P3AS09R709730DE010 E3DLP1MW

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 46.1   | 9.8       |
| 10°-20°   | 114.0  | 24.2      |
| 20°-30°   | 129.8  | 27.5      |
| 30°-40°   | 101.5  | 21.5      |
| 40°-50°   | 49.9   | 10.6      |
| 50°-60°   | 15.3   | 3.2       |
| 60°-70°   | 9.1    | 1.9       |
| 70°-80°   | 4.9    | 1.0       |
| 80°-90°   | 1.4    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 289.9  | 61.4      |
| 0°-40°    | 391.4  | 82.9      |
| 0°-60°    | 456.6  | 96.7      |
| 0°-90°    | 472.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 472.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 505 |      |
| 5°  | 494 | 46   |
| 15° | 410 | 114  |
| 25° | 284 | 130  |
| 35° | 163 | 102  |
| 45° | 64  | 50   |
| 55° | 16  | 15   |
| 65° | 9   | 9    |
| 75° | 5   | 5    |
| 85° | 1   | 1    |
| 90° | 0   |      |

TEST NUMBER: P1264888

CATALOG NUMBER: P3AS09R709730DE010 E3DLP1MW

**CANDELA DISTRIBUTION (FULL):**

|       | 0°    |
|-------|-------|
| 0°    | 504.9 |
| 2.5°  | 502.3 |
| 5°    | 493.7 |
| 7.5°  | 479.9 |
| 10°   | 460.2 |
| 12.5° | 437.3 |
| 15°   | 409.7 |
| 17.5° | 380.1 |
| 20°   | 348.6 |
| 22.5° | 315.8 |
| 25°   | 283.6 |
| 27.5° | 252.1 |
| 30°   | 221.9 |
| 32.5° | 191.7 |
| 35°   | 162.8 |
| 37.5° | 135.3 |
| 40°   | 109.0 |
| 42.5° | 84.7  |
| 45°   | 63.7  |
| 47.5° | 44.6  |
| 50°   | 28.9  |
| 52.5° | 19.0  |
| 55°   | 15.8  |
| 57.5° | 13.8  |
| 60°   | 11.8  |
| 62.5° | 10.5  |
| 65°   | 9.2   |
| 67.5° | 7.9   |
| 70°   | 6.6   |
| 72.5° | 5.3   |
| 75°   | 4.6   |
| 77.5° | 3.9   |
| 80°   | 2.6   |
| 82.5° | 2.0   |
| 85°   | 1.3   |
| 87.5° | 0.7   |
| 90°   | 0.0   |

(END OF REPORT)