

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1265238

Luminaire Tested: P3AS13R609730DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1265238
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-38)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R609730DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R60 optic, 3000K CCT AND, 97CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 352.0 lumens
Efficiency: N/A
Efficacy: 24.1 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1265238

CATALOG NUMBER: P3AS13R609730DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1265238

CATALOG NUMBER: P3AS13R609730DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	62495
5°	61787
10°	59652
15°	56345
20°	51945
25°	47035
30°	41753
35°	35683
40°	28367
45°	20002
50°	11940
55°	6040
60°	5789
65°	5344
70°	4937
75°	4745
80°	4293
85°	3271

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 20002 cd/sqm

TEST NUMBER: P1265238

CATALOG NUMBER: P3AS13R609730DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	26.4	7.5
10°-20°	69.4	19.7
20°-30°	89.1	25.3
30°-40°	82.6	23.5
40°-50°	50.3	14.3
50°-60°	16.7	4.8
60°-70°	10.2	2.9
70°-80°	5.8	1.6
80°-90°	1.6	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	184.8	52.5
0°-40°	267.4	76.0
0°-60°	334.4	95.0
0°-90°	352.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	352.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	285	
5°	281	26
15°	248	69
25°	194	89
35°	133	83
45°	64	50
55°	16	17
65°	10	10
75°	6	6
85°	1	2
90°	0	

TEST NUMBER: P1265238

CATALOG NUMBER: P3AS13R609730DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	285.0
2.5°	283.7
5°	280.7
7.5°	275.1
10°	267.9
12.5°	258.9
15°	248.2
17.5°	235.8
20°	222.6
22.5°	208.5
25°	194.4
27.5°	179.9
30°	164.9
32.5°	150.0
35°	133.3
37.5°	115.8
40°	99.1
42.5°	81.6
45°	64.5
47.5°	50.0
50°	35.0
52.5°	20.9
55°	15.8
57.5°	14.5
60°	13.2
62.5°	11.5
65°	10.3
67.5°	9.0
70°	7.7
72.5°	6.4
75°	5.6
77.5°	4.3
80°	3.4
82.5°	2.1
85°	1.3
87.5°	0.9
90°	0.0

(END OF REPORT)