

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1265246

Luminaire Tested: P3AS13R609730DE010 E3DLP1LI

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1265246  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-37)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS13R609730DE010 E3DLP1LI  
Description: 3in Adjustable LED luminaire with, R60 optic, 3000K CCT AND, 97CRI , E3DLP1LI TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 634.0 lumens  
Efficiency: N/A  
Efficacy: 43.4 lumens/watt  
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 14.6  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1265246

CATALOG NUMBER: P3AS13R609730DE010 E3DLP1LI

### Luminous Intensity Polar Plot



TEST NUMBER: P1265246

CATALOG NUMBER: P3AS13R609730DE010 E3DLP1LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 107 | 105 | 110 | 108 | 105 | 103 | 104 | 102 | 100 |  | 100 | 98  | 97  |  | 96  |
| 2   | 107 | 101 | 97  | 93  | 104 | 100 | 96  | 92  | 96  | 93  | 90  |  | 93  | 91  | 88  |  | 91  |
| 3   | 101 | 94  | 88  | 84  | 99  | 92  | 87  | 83  | 90  | 86  | 82  |  | 87  | 84  | 81  |  | 85  |
| 4   | 95  | 87  | 81  | 77  | 93  | 86  | 80  | 76  | 84  | 79  | 75  |  | 82  | 78  | 74  |  | 80  |
| 5   | 90  | 81  | 75  | 70  | 88  | 80  | 74  | 70  | 78  | 73  | 69  |  | 77  | 72  | 69  |  | 75  |
| 6   | 85  | 76  | 69  | 65  | 84  | 75  | 69  | 65  | 73  | 68  | 64  |  | 72  | 67  | 64  |  | 71  |
| 7   | 81  | 71  | 65  | 60  | 79  | 70  | 64  | 60  | 69  | 64  | 60  |  | 68  | 63  | 59  |  | 67  |
| 8   | 77  | 67  | 60  | 56  | 75  | 66  | 60  | 56  | 65  | 60  | 56  |  | 64  | 59  | 55  |  | 63  |
| 9   | 73  | 63  | 57  | 52  | 72  | 62  | 56  | 52  | 61  | 56  | 52  |  | 60  | 55  | 52  |  | 60  |
| 10  | 69  | 59  | 53  | 49  | 68  | 59  | 53  | 49  | 58  | 53  | 49  |  | 57  | 52  | 49  |  | 56  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 160667 |
| 5°  | 157076 |
| 10° | 147047 |
| 15° | 131919 |
| 20° | 113457 |
| 25° | 93804  |
| 30° | 74113  |
| 35° | 55038  |
| 40° | 37900  |
| 45° | 23785  |
| 50° | 13066  |
| 55° | 7646   |
| 60° | 6885   |
| 65° | 5863   |
| 70° | 5001   |
| 75° | 5168   |
| 80° | 4420   |
| 85° | 4277   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 23785 cd/sqm

TEST NUMBER: P1265246

CATALOG NUMBER: P3AS13R609730DE010 E3DLP1LI

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 66.4   | 10.5      |
| 10°-20°   | 161.4  | 25.5      |
| 20°-30°   | 177.0  | 27.9      |
| 30°-40°   | 129.0  | 20.3      |
| 40°-50°   | 60.9   | 9.6       |
| 50°-60°   | 19.9   | 3.1       |
| 60°-70°   | 11.3   | 1.8       |
| 70°-80°   | 6.1    | 1.0       |
| 80°-90°   | 1.9    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 404.9  | 63.9      |
| 0°-40°    | 533.8  | 84.2      |
| 0°-60°    | 614.7  | 97.0      |
| 0°-90°    | 634.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 634.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 733 |      |
| 5°  | 714 | 66   |
| 15° | 581 | 161  |
| 25° | 388 | 177  |
| 35° | 206 | 129  |
| 45° | 77  | 61   |
| 55° | 20  | 20   |
| 65° | 11  | 11   |
| 75° | 6   | 6    |
| 85° | 2   | 2    |
| 90° | 0   |      |

TEST NUMBER: P1265246

CATALOG NUMBER: P3AS13R609730DE010 E3DLP1LI

**CANDELA DISTRIBUTION (FULL):**

| 0°    |       |
|-------|-------|
| 0°    | 732.7 |
| 2.5°  | 728.4 |
| 5°    | 713.6 |
| 7.5°  | 690.9 |
| 10°   | 660.4 |
| 12.5° | 623.8 |
| 15°   | 581.1 |
| 17.5° | 535.0 |
| 20°   | 486.2 |
| 22.5° | 436.5 |
| 25°   | 387.7 |
| 27.5° | 338.9 |
| 30°   | 292.7 |
| 32.5° | 248.3 |
| 35°   | 205.6 |
| 37.5° | 167.3 |
| 40°   | 132.4 |
| 42.5° | 101.9 |
| 45°   | 76.7  |
| 47.5° | 55.8  |
| 50°   | 38.3  |
| 52.5° | 25.3  |
| 55°   | 20.0  |
| 57.5° | 17.4  |
| 60°   | 15.7  |
| 62.5° | 13.1  |
| 65°   | 11.3  |
| 67.5° | 9.6   |
| 70°   | 7.8   |
| 72.5° | 7.0   |
| 75°   | 6.1   |
| 77.5° | 4.4   |
| 80°   | 3.5   |
| 82.5° | 2.6   |
| 85°   | 1.7   |
| 87.5° | 0.9   |
| 90°   | 0.0   |

(END OF REPORT)