

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1265509

Luminaire Tested: P3AS17R509730DE010 E3CB1MMS

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1265509
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-32)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R509730DE010 E3CB1MMS
Description: 3in Adjustable LED luminaire with, R50 optic, 3000K CCT AND, 97CRI , E3CB1MMS TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1580.1 lumens
Efficiency: N/A
Efficacy: 74.5 lumens/watt
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.76
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1265509

CATALOG NUMBER: P3AS17R509730DE010 E3CB1MMS

Luminous Intensity Polar Plot



TEST NUMBER: P1265509

CATALOG NUMBER: P3AS17R509730DE010 E3CB1MMS

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	109	107	112	109	107	106	105	104	102		102	101	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	105	99	95	91	103	98	94	90	95	92	89		93	90	88		91
4	100	94	89	85	99	92	88	85	90	87	84		88	85	83		87
5	96	89	84	80	94	88	83	79	86	82	79		84	81	78		83
6	92	84	79	75	91	83	79	75	82	78	74		81	77	74		79
7	88	80	75	71	87	79	74	71	78	74	71		77	73	70		76
8	85	76	71	67	83	76	71	67	75	70	67		74	70	67		73
9	81	73	68	64	80	72	67	64	71	67	64		71	66	63		70
10	78	69	64	61	77	69	64	61	68	64	61		68	63	61		67

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	550263
5°	540412
10°	518895
15°	475826
20°	419570
25°	321599
30°	174862
35°	56269
40°	13225
45°	1799
50°	1569
55°	1759
60°	1535
65°	1816
70°	1475
75°	1949
80°	1515
85°	3019

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 85°

Luminance: 3019 cd/sqm

TEST NUMBER: P1265509

CATALOG NUMBER: P3AS17R509730DE010 E3CB1MMS

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	230.4	14.6
10°-20°	582.6	36.9
20°-30°	583.5	36.9
30°-40°	164.1	10.4
40°-50°	9.9	0.6
50°-60°	3.7	0.2
60°-70°	3.0	0.2
70°-80°	2.0	0.1
80°-90°	0.8	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1396.5	88.4
0°-40°	1560.6	98.8
0°-60°	1574.2	99.6
0°-90°	1580.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1580.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2509	
5°	2455	230
15°	2096	583
25°	1329	584
35°	210	164
45°	6	10
55°	5	4
65°	4	3
75°	2	2
85°	1	1
90°	0	

TEST NUMBER: P1265509

CATALOG NUMBER: P3AS17R509730DE010 E3CB1MMS

CANDELA DISTRIBUTION (FULL):

0°	
0°	2509.4
2.5°	2496.7
5°	2455.1
7.5°	2398.6
10°	2330.4
12.5°	2227.6
15°	2096.0
17.5°	1944.7
20°	1798.0
22.5°	1615.6
25°	1329.2
27.5°	989.7
30°	690.6
32.5°	416.9
35°	210.2
37.5°	99.3
40°	46.2
42.5°	17.3
45°	5.8
47.5°	4.6
50°	4.6
52.5°	4.6
55°	4.6
57.5°	3.5
60°	3.5
62.5°	3.5
65°	3.5
67.5°	2.3
70°	2.3
72.5°	2.3
75°	2.3
77.5°	1.2
80°	1.2
82.5°	1.2
85°	1.2
87.5°	0.0
90°	0.0

(END OF REPORT)