

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1265541

Luminaire Tested: P3AS17R559730DE010 E3CD1MMS

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1265541
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-36)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R559730DE010 E3CD1MMS
Description: 3in Adjustable LED luminaire with, R55 optic, 3000K CCT AND, 97CRI , E3CD1MMS TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1536.0 lumens
Efficiency: N/A
Efficacy: 72.5 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.82
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1265541

CATALOG NUMBER: P3AS17R559730DE010 E3CD1MMS

Luminous Intensity Polar Plot



TEST NUMBER: P1265541

CATALOG NUMBER: P3AS17R559730DE010 E3CD1MMS

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	112	109	107	105	105	104	102		101	100	99		98
2	109	104	101	98	107	103	99	96	100	97	94		97	94	92		94
3	104	98	94	90	102	97	93	89	94	91	88		92	89	86		90
4	99	92	87	84	98	91	87	83	89	85	82		87	84	81		85
5	95	87	82	78	93	86	81	78	85	80	77		83	79	76		82
6	91	83	77	73	89	82	77	73	80	76	72		79	75	72		78
7	87	78	73	69	85	78	72	69	76	72	68		75	71	68		74
8	83	74	69	65	82	74	68	65	73	68	65		72	67	64		71
9	79	71	65	61	78	70	65	61	69	64	61		68	64	61		68
10	76	67	62	58	75	67	62	58	66	61	58		65	61	58		65

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	426018
5°	422055
10°	439025
15°	432920
20°	399221
25°	324817
30°	197296
35°	68288
40°	19494
45°	9303
50°	3923
55°	1759
60°	2017
65°	1816
70°	1475
75°	1949
80°	1515
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 9303 cd/sqm

TEST NUMBER: P1265541

CATALOG NUMBER: P3AS17R559730DE010 E3CD1MMS

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	185.4	12.1
10°-20°	530.0	34.5
20°-30°	590.9	38.5
30°-40°	193.3	12.6
40°-50°	25.5	1.7
50°-60°	5.4	0.3
60°-70°	3.1	0.2
70°-80°	2.0	0.1
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1306.3	85.0
0°-40°	1499.5	97.6
0°-60°	1530.4	99.6
0°-90°	1536.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1536.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1943	
5°	1917	185
15°	1907	530
25°	1342	591
35°	255	193
45°	30	25
55°	5	5
65°	4	3
75°	2	2
85°	0	0
90°	0	

TEST NUMBER: P1265541

CATALOG NUMBER: P3AS17R559730DE010 E3CD1MMS

CANDELA DISTRIBUTION (FULL):

0°	
0°	1942.8
2.5°	1928.9
5°	1917.4
7.5°	1945.1
10°	1971.7
12.5°	1957.8
15°	1907.0
17.5°	1826.2
20°	1710.8
22.5°	1551.5
25°	1342.5
27.5°	1077.0
30°	779.2
32.5°	477.9
35°	255.1
37.5°	129.3
40°	68.1
42.5°	43.9
45°	30.0
47.5°	20.8
50°	11.5
52.5°	6.9
55°	4.6
57.5°	4.6
60°	4.6
62.5°	3.5
65°	3.5
67.5°	2.3
70°	2.3
72.5°	2.3
75°	2.3
77.5°	1.2
80°	1.2
82.5°	1.2
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)