

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1265583

Luminaire Tested: P3AS17R609730DE010 E3DLD1GPH

Issue Date: 1/30/2026

**Test Information**


Test Method: LM-79-2019  
Report Number: P1265583  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-38)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS17R609730DE010 E3DLD1GPH  
Description: 3in Adjustable LED luminaire with, R60 optic, 3000K CCT AND, 97CRI , E3DLD1GPH TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 466.0 lumens  
Efficiency: N/A  
Efficacy: 22.0 lumens/watt  
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 21.2  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1265583  
CATALOG NUMBER: P3AS17R609730DE010 E3DLD1GPH

### Luminous Intensity Polar Plot





TEST NUMBER: P1265583  
 CATALOG NUMBER: P3AS17R609730DE010 E3DLD1GPH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	112	109	106	103	110	107	104	101	102	100	98	99	97	95	95	94	93	91	91	91	91
2	105	99	94	90	103	97	93	89	94	90	87	91	88	85	88	86	84	82	82	82	82
3	99	91	85	80	96	89	84	79	87	82	78	84	80	77	82	78	76	74	74	74	74
4	92	83	77	72	90	82	76	71	80	75	70	78	73	70	76	72	69	67	67	67	67
5	87	77	70	65	85	76	69	65	74	68	64	72	67	63	71	66	63	61	61	61	61
6	82	71	64	59	80	70	64	59	69	63	58	67	62	58	66	61	58	56	56	56	56
7	77	66	59	54	75	65	59	54	64	58	54	63	57	53	61	57	53	51	51	51	51
8	72	61	55	50	71	61	54	50	60	54	49	59	53	49	58	53	49	47	47	47	47
9	68	57	51	46	67	57	50	46	56	50	46	55	49	46	54	49	45	44	44	44	44
10	65	54	47	43	64	53	47	43	52	47	43	52	46	42	51	46	42	41	41	41	41

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	82713
5°	81796
10°	78956
15°	74597
20°	68769
25°	62254
30°	55274
35°	47248
40°	37556
45°	26483
50°	15829
55°	7990
60°	7675
65°	7057
70°	6540
75°	6270
80°	5683
85°	4277

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 26483 cd/sqm



TEST NUMBER: P1265583  
 CATALOG NUMBER: P3AS17R609730DE010 E3DLD1GPH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	34.9	7.5
10°-20°	91.8	19.7
20°-30°	117.9	25.3
30°-40°	109.3	23.5
40°-50°	66.6	14.3
50°-60°	22.2	4.8
60°-70°	13.5	2.9
70°-80°	7.6	1.6
80°-90°	2.1	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	244.7	52.5
0°-40°	354.0	76.0
0°-60°	442.7	95.0
0°-90°	466.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	466.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	377	
5°	372	35
15°	329	92
25°	257	118
35°	176	109
45°	85	67
55°	21	22
65°	14	14
75°	7	8
85°	2	2
90°	0	



TEST NUMBER: P1265583  
CATALOG NUMBER: P3AS17R609730DE010 E3DLD1GPH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	377.2
2.5°	375.5
5°	371.6
7.5°	364.2
10°	354.6
12.5°	342.7
15°	328.6
17.5°	312.2
20°	294.7
22.5°	276.0
25°	257.3
27.5°	238.1
30°	218.3
32.5°	198.5
35°	176.5
37.5°	153.3
40°	131.2
42.5°	108.0
45°	85.4
47.5°	66.2
50°	46.4
52.5°	27.7
55°	20.9
57.5°	19.2
60°	17.5
62.5°	15.3
65°	13.6
67.5°	11.9
70°	10.2
72.5°	8.5
75°	7.4
77.5°	5.7
80°	4.5
82.5°	2.8
85°	1.7
87.5°	1.1
90°	0.0

(END OF REPORT)