

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1265763

Luminaire Tested: P3AS20R259730D010 E3DLP1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1265763
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-9)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R259730D010 E3DLP1GPH
Description: 3in Adjustable LED luminaire with, R25 optic, 3000K CCT AND, 97CRI , E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 476.0 lumens
Efficiency: N/A
Efficacy: 16.5 lumens/watt
Spacing Criteria (0/90/45): 0.62 / 0.62 / 0.68
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1265763

CATALOG NUMBER: P3AS20R259730D010 E3DLP1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1265763

CATALOG NUMBER: P3AS20R259730D010 E3DLP1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	101		100	99	98		97
2	107	102	98	95	105	101	97	94	97	94	92		94	92	90		92
3	102	95	90	86	100	94	89	86	91	87	84		89	86	83		87
4	97	89	84	79	95	88	83	79	86	81	78		84	80	77		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74
7	84	74	68	64	82	74	68	64	72	67	64		71	67	63		70
8	80	70	65	60	79	70	64	60	69	64	60		68	63	60		67
9	76	67	61	57	75	66	61	57	65	60	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	172815
5°	165793
10°	145243
15°	116754
20°	89701
25°	67867
30°	49046
35°	32578
40°	19751
45°	11505
50°	7335
55°	5964
60°	5219
65°	4618
70°	3783
75°	3813
80°	2778
85°	3774

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 11505 cd/sqm

TEST NUMBER: P1265763

CATALOG NUMBER: P3AS20R259730D010 E3DLP1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	68.6	14.4
10°-20°	142.2	29.9
20°-30°	128.6	27.0
30°-40°	77.2	16.2
40°-50°	30.7	6.4
50°-60°	14.2	3.0
60°-70°	8.6	1.8
70°-80°	4.6	1.0
80°-90°	1.3	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	339.4	71.3
0°-40°	416.6	87.5
0°-60°	461.5	97.0
0°-90°	476.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	476.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	788	
5°	753	69
15°	514	142
25°	280	129
35°	122	77
45°	37	31
55°	16	14
65°	9	9
75°	4	5
85°	2	1
90°	0	

TEST NUMBER: P1265763

CATALOG NUMBER: P3AS20R259730D010 E3DLP1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	788.1
1°	788.1
2°	784.4
3°	776.2
4°	765.8
5°	753.2
6°	736.9
7°	718.3
8°	696.8
9°	675.3
10°	652.3
11°	625.6
12°	598.1
13°	570.7
14°	543.2
15°	514.3
17.5°	446.0
20°	384.4
22.5°	328.7
25°	280.5
27.5°	235.2
30°	193.7
32.5°	155.8
35°	121.7
37.5°	92.8
40°	69.0
42.5°	50.5
45°	37.1
47.5°	28.2
50°	21.5
52.5°	17.8
55°	15.6
57.5°	13.4
60°	11.9
62.5°	9.6
65°	8.9
67.5°	7.4
70°	5.9
72.5°	5.2
75°	4.5
77.5°	3.7
80°	2.2
82.5°	1.5
85°	1.5
87.5°	0.7



TEST NUMBER: P1265763

CATALOG NUMBER: P3AS20R259730D010 E3DLP1GPH

CANDELA DISTRIBUTION (continued):



(END OF REPORT)