

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1265789

Luminaire Tested: P3AS20R309730D010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1265789
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-14)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R309730D010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R30 optic, 3000K CCT AND, 97CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 605.0 lumens
Efficiency: N/A
Efficacy: 21.0 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1265789

CATALOG NUMBER: P3AS20R309730D010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1265789

CATALOG NUMBER: P3AS20R309730D010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	82	88	84	80		86	82	79		84
4	94	85	79	74	92	84	79	74	82	77	73		80	76	72		78
5	89	79	73	68	87	78	72	68	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	62		70	65	61		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	54	74	64	58	53	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57
10	68	57	51	47	67	57	51	47	56	50	47		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	142927
5°	139709
10°	129924
15°	115619
20°	99432
25°	84247
30°	69935
35°	54850
40°	39302
45°	25770
50°	14703
55°	9634
60°	9122
65°	8457
70°	7629
75°	6947
80°	6566
85°	5535

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 25770 cd/sqm

TEST NUMBER: P1265789

CATALOG NUMBER: P3AS20R309730D010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	58.9	9.7
10°-20°	141.6	23.4
20°-30°	159.6	26.4
30°-40°	127.4	21.1
40°-50°	65.5	10.8
50°-60°	24.6	4.1
60°-70°	16.2	2.7
70°-80°	8.7	1.4
80°-90°	2.5	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	360.1	59.5
0°-40°	487.5	80.6
0°-60°	577.6	95.5
0°-90°	605.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	605.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	652	
5°	635	59
15°	509	142
25°	348	160
35°	205	127
45°	83	65
55°	25	25
65°	16	16
75°	8	9
85°	2	3
90°	0	

TEST NUMBER: P1265789

CATALOG NUMBER: P3AS20R309730D010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	651.8
1°	651.8
2°	649.6
3°	645.9
4°	640.7
5°	634.7
6°	627.3
7°	617.7
8°	607.3
9°	595.4
10°	583.5
11°	570.2
12°	556.1
13°	541.2
14°	525.6
15°	509.3
17.5°	467.7
20°	426.1
22.5°	386.0
25°	348.2
27.5°	311.1
30°	276.2
32.5°	240.5
35°	204.9
37.5°	170.0
40°	137.3
42.5°	108.4
45°	83.1
47.5°	61.6
50°	43.1
52.5°	30.4
55°	25.2
57.5°	23.0
60°	20.8
62.5°	18.6
65°	16.3
67.5°	14.1
70°	11.9
72.5°	9.7
75°	8.2
77.5°	6.7
80°	5.2
82.5°	3.7
85°	2.2
87.5°	0.7



TEST NUMBER: P1265789

CATALOG NUMBER: P3AS20R309730D010 E3DLD1GPH

CANDELA DISTRIBUTION (continued):



(END OF REPORT)