

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1266251

Luminaire Tested: P3AS02R309735DE010 E3DLP1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1266251
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-13)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R309735DE010 E3DLP1GPH
Description: 3in Adjustable LED luminaire with, R30 optic, 3500K CCT AND, 97CRI , E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 72.0 lumens
Efficiency: N/A
Efficacy: 20.0 lumens/watt
Spacing Criteria (0/90/45): 0.66 / 0.66 / 0.7
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1266251

CATALOG NUMBER: P3AS02R309735DE010 E3DLP1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1266251

CATALOG NUMBER: P3AS02R309735DE010 E3DLP1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	101		100	99	98		97
2	107	102	98	95	105	101	97	94	97	94	92		94	92	90		92
3	102	95	90	86	100	94	89	85	91	87	84		89	86	83		87
4	97	89	84	79	95	88	83	79	86	81	78		84	80	77		82
5	92	84	78	73	90	83	77	73	81	76	72		79	75	72		78
6	88	79	73	68	86	78	72	68	76	71	68		75	71	67		74
7	83	74	68	64	82	74	68	64	72	67	63		71	67	63		70
8	80	70	64	60	78	70	64	60	69	63	60		68	63	60		67
9	76	67	61	57	75	66	60	57	65	60	56		64	60	56		63
10	73	63	58	54	72	63	57	54	62	57	54		61	57	53		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	24603
5°	23839
10°	21487
15°	17775
20°	13745
25°	10307
30°	7495
35°	4979
40°	3063
45°	1799
50°	1092
55°	879
60°	789
65°	623
70°	577
75°	593
80°	379
85°	503

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1799 cd/sqm

TEST NUMBER: P1266251

CATALOG NUMBER: P3AS02R309735DE010 E3DLP1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	10.0	13.8
10°-20°	21.6	29.9
20°-30°	19.6	27.2
30°-40°	11.9	16.5
40°-50°	4.8	6.6
50°-60°	2.1	2.9
60°-70°	1.3	1.8
70°-80°	0.7	1.0
80°-90°	0.2	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	51.1	71.0
0°-40°	63.0	87.5
0°-60°	69.8	97.0
0°-90°	72.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	72.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	112	
5°	108	10
15°	78	22
25°	43	20
35°	19	12
45°	6	5
55°	2	2
65°	1	1
75°	1	1
85°	0	0
90°	0	

TEST NUMBER: P1266251

CATALOG NUMBER: P3AS02R309735DE010 E3DLP1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	112.2
1°	112.1
2°	111.6
3°	110.9
4°	109.7
5°	108.3
6°	106.5
7°	104.6
8°	102.2
9°	99.4
10°	96.5
11°	93.1
12°	89.5
13°	86.0
14°	82.1
15°	78.3
17.5°	68.3
20°	58.9
22.5°	50.2
25°	42.6
27.5°	35.7
30°	29.6
32.5°	23.9
35°	18.6
37.5°	14.3
40°	10.7
42.5°	7.8
45°	5.8
47.5°	4.4
50°	3.2
52.5°	2.6
55°	2.3
57.5°	2.0
60°	1.8
62.5°	1.5
65°	1.2
67.5°	1.1
70°	0.9
72.5°	0.8
75°	0.7
77.5°	0.6
80°	0.3
82.5°	0.2
85°	0.2
87.5°	0.1



TEST NUMBER: P1266251

CATALOG NUMBER: P3AS02R309735DE010 E3DLP1GPH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)