

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1266445

Luminaire Tested: P3AS02R659735DE010 E3DL1WMH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1266445
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-43)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R659735DE010 E3DL1WMH
Description: 3in Adjustable LED luminaire with, R65 optic, 3500K CCT AND, 97CRI , E3DL1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 228.0 lumens
Efficiency: N/A
Efficacy: 63.3 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1266445

CATALOG NUMBER: P3AS02R659735DE010 E3DL1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1266445

CATALOG NUMBER: P3AS02R659735DE010 E3DL1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	106	103	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	95	89	85	99	93	88	84	90	86	83		88	85	82		86
4	96	88	82	78	94	87	81	77	85	80	76		83	79	75		81
5	91	82	76	71	89	81	75	71	79	74	70		77	73	70		76
6	86	77	70	66	84	76	70	66	74	69	65		73	68	65		72
7	82	72	66	61	80	71	65	61	70	64	61		69	64	60		67
8	77	67	61	57	76	67	61	57	66	60	57		65	60	56		64
9	74	64	57	53	72	63	57	53	62	57	53		61	56	53		60
10	70	60	54	50	69	59	54	50	59	53	50		58	53	50		57

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	53768
5°	53115
10°	51101
15°	47878
20°	43054
25°	36559
30°	28587
35°	20371
40°	13339
45°	8249
50°	4196
55°	1491
60°	1316
65°	1297
70°	1154
75°	1186
80°	1137
85°	1258

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 8249 cd/sqm

TEST NUMBER: P1266445

CATALOG NUMBER: P3AS02R659735DE010 E3DL1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	22.7	9.9
10°-20°	58.7	25.7
20°-30°	68.6	30.1
30°-40°	47.9	21.0
40°-50°	21.1	9.3
50°-60°	4.7	2.1
60°-70°	2.4	1.0
70°-80°	1.4	0.6
80°-90°	0.5	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	149.9	65.8
0°-40°	197.9	86.8
0°-60°	223.7	98.1
0°-90°	228.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	228.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	245	
5°	241	23
15°	211	59
25°	151	69
35°	76	48
45°	27	21
55°	4	5
65°	2	2
75°	1	1
85°	0	1
90°	0	

TEST NUMBER: P1266445

CATALOG NUMBER: P3AS02R659735DE010 E3DL1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	245.2
2.5°	244.3
5°	241.3
7.5°	236.3
10°	229.5
12.5°	221.1
15°	210.9
17.5°	198.4
20°	184.5
22.5°	168.8
25°	151.1
27.5°	132.5
30°	112.9
32.5°	94.1
35°	76.1
37.5°	60.4
40°	46.6
42.5°	35.2
45°	26.6
47.5°	19.5
50°	12.3
52.5°	6.4
55°	3.9
57.5°	3.4
60°	3.0
62.5°	2.7
65°	2.5
67.5°	2.0
70°	1.8
72.5°	1.6
75°	1.4
77.5°	1.1
80°	0.9
82.5°	0.7
85°	0.5
87.5°	0.2
90°	0.0

(END OF REPORT)