

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1266606

Luminaire Tested: P3AS05R209735DE010 E3PHLP1MW

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1266606
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2509-551-6)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R209735DE010 E3PHLP1MW
Description: 3in Adjustable LED luminaire with, R20 optic, 3500K CCT AND, 97CRI , E3PHLP1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 228.0 lumens
Efficiency: N/A
Efficacy: 31.7 lumens/watt
Spacing Criteria (0/90/45): 0.55 / 0.55 / 0.63
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1266606

CATALOG NUMBER: P3AS05R209735DE010 E3PHLP1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1266606

CATALOG NUMBER: P3AS05R209735DE010 E3PHLP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	108	105	102	109	106	103	101	102	100	97		98	96	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	97	90	84	80	87	82	78		84	80	77		82
4	93	84	78	73	91	83	77	73	81	76	72		79	74	71		77
5	88	79	72	67	86	78	71	67	76	70	66		74	69	66		72
6	84	74	67	62	82	73	66	62	71	66	61		70	65	61		68
7	79	69	63	58	78	68	62	58	67	62	57		66	61	57		65
8	76	65	59	54	74	65	58	54	64	58	54		62	57	54		61
9	72	62	55	51	71	61	55	51	60	55	51		59	54	51		58
10	69	59	52	48	68	58	52	48	57	52	48		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	81090
5°	75633
10°	62747
15°	47991
20°	36006
25°	27123
30°	20054
35°	14000
40°	9618
45°	6667
50°	5731
55°	5658
60°	5877
65°	5915
70°	6027
75°	6270
80°	6819
85°	6793

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 82.5°

Luminance: 7896 cd/sqm

TEST NUMBER: P1266606

CATALOG NUMBER: P3AS05R209735DE010 E3PHLP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	30.8	13.5
10°-20°	58.8	25.8
20°-30°	51.7	22.7
30°-40°	33.4	14.6
40°-50°	17.7	7.8
50°-60°	13.3	5.8
60°-70°	11.3	5.0
70°-80°	8.0	3.5
80°-90°	3.1	1.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	141.3	62.0
0°-40°	174.6	76.6
0°-60°	205.6	90.2
0°-90°	228.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	228.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	370	
5°	344	31
15°	211	59
25°	112	52
35°	52	33
45°	22	18
55°	15	13
65°	11	11
75°	7	8
85°	3	3
90°	0	

TEST NUMBER: P1266606

CATALOG NUMBER: P3AS05R209735DE010 E3PHLP1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	369.8
2.5°	362.4
5°	343.6
7.5°	314.7
10°	281.8
12.5°	245.6
15°	211.4
17.5°	180.5
20°	154.3
22.5°	132.2
25°	112.1
27.5°	94.6
30°	79.2
32.5°	65.1
35°	52.3
37.5°	42.3
40°	33.6
42.5°	26.8
45°	21.5
47.5°	18.8
50°	16.8
52.5°	15.4
55°	14.8
57.5°	14.1
60°	13.4
62.5°	12.1
65°	11.4
67.5°	10.7
70°	9.4
72.5°	8.7
75°	7.4
77.5°	6.7
80°	5.4
82.5°	4.7
85°	2.7
87.5°	1.3
90°	0.0

(END OF REPORT)