

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1267047

Luminaire Tested: P3AS09R309735DE010 E3PHLD1MW

Issue Date: 1/29/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1267047  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2509-551-12)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/29/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS09R309735DE010 E3PHLD1MW  
Description: 3in Adjustable LED luminaire with, R30 optic, 3500K CCT AND, 97CRI , E3PHLD1MW TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 530.0 lumens  
Efficiency: N/A  
Efficacy: 47.8 lumens/watt  
Spacing Criteria (0/90/45): 0.65 / 0.65 / 0.74  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 11.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1267047

CATALOG NUMBER: P3AS09R309735DE010 E3PHLD1MW

### Luminous Intensity Polar Plot



TEST NUMBER: P1267047

CATALOG NUMBER: P3AS09R309735DE010 E3PHLD1MW

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 112 | 108 | 105 | 102 | 109 | 106 | 103 | 100 | 102 | 99  | 97  |  | 98  | 96  | 94  |  | 94  |
| 2   | 104 | 98  | 93  | 88  | 102 | 96  | 91  | 87  | 93  | 89  | 85  |  | 90  | 86  | 83  |  | 87  |
| 3   | 97  | 89  | 83  | 78  | 95  | 88  | 82  | 77  | 85  | 80  | 76  |  | 82  | 78  | 74  |  | 80  |
| 4   | 91  | 82  | 75  | 69  | 89  | 80  | 74  | 69  | 78  | 72  | 68  |  | 76  | 71  | 67  |  | 74  |
| 5   | 85  | 75  | 68  | 63  | 84  | 74  | 67  | 62  | 72  | 66  | 62  |  | 70  | 65  | 61  |  | 69  |
| 6   | 80  | 69  | 62  | 57  | 79  | 69  | 62  | 57  | 67  | 61  | 56  |  | 65  | 60  | 56  |  | 64  |
| 7   | 76  | 65  | 57  | 52  | 74  | 64  | 57  | 52  | 62  | 56  | 52  |  | 61  | 56  | 52  |  | 60  |
| 8   | 71  | 60  | 53  | 48  | 70  | 60  | 53  | 48  | 58  | 52  | 48  |  | 57  | 52  | 48  |  | 56  |
| 9   | 68  | 57  | 50  | 45  | 66  | 56  | 49  | 45  | 55  | 49  | 45  |  | 54  | 49  | 45  |  | 53  |
| 10  | 64  | 53  | 47  | 42  | 63  | 53  | 46  | 42  | 52  | 46  | 42  |  | 51  | 46  | 42  |  | 50  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 130604 |
| 5°  | 124829 |
| 10° | 107658 |
| 15° | 89240  |
| 20° | 73156  |
| 25° | 58963  |
| 30° | 47526  |
| 35° | 38949  |
| 40° | 32346  |
| 45° | 27445  |
| 50° | 23470  |
| 55° | 20300  |
| 60° | 18113  |
| 65° | 15825  |
| 70° | 13848  |
| 75° | 11692  |
| 80° | 8713   |
| 85° | 5032   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 27445 cd/sqm

TEST NUMBER: P1267047

CATALOG NUMBER: P3AS09R309735DE010 E3PHLD1MW

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 51.4   | 9.7       |
| 10°-20°   | 109.6  | 20.7      |
| 20°-30°   | 112.4  | 21.2      |
| 30°-40°   | 91.8   | 17.3      |
| 40°-50°   | 68.7   | 13.0      |
| 50°-60°   | 48.3   | 9.1       |
| 60°-70°   | 30.4   | 5.7       |
| 70°-80°   | 14.6   | 2.8       |
| 80°-90°   | 2.8    | 0.5       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 273.4  | 51.6      |
| 0°-40°    | 365.2  | 68.9      |
| 0°-60°    | 482.2  | 91.0      |
| 0°-90°    | 530.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 530.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 596 |      |
| 5°  | 567 | 51   |
| 15° | 393 | 110  |
| 25° | 244 | 112  |
| 35° | 146 | 92   |
| 45° | 88  | 69   |
| 55° | 53  | 48   |
| 65° | 30  | 30   |
| 75° | 14  | 15   |
| 85° | 2   | 3    |
| 90° | 0   |      |

TEST NUMBER: P1267047

CATALOG NUMBER: P3AS09R309735DE010 E3PHLD1MW

**CANDELA DISTRIBUTION (FULL):**

| 0°    |       |
|-------|-------|
| 0°    | 595.6 |
| 2.5°  | 589.7 |
| 5°    | 567.1 |
| 7.5°  | 529.7 |
| 10°   | 483.5 |
| 12.5° | 438.3 |
| 15°   | 393.1 |
| 17.5° | 351.8 |
| 20°   | 313.5 |
| 22.5° | 277.2 |
| 25°   | 243.7 |
| 27.5° | 214.3 |
| 30°   | 187.7 |
| 32.5° | 166.1 |
| 35°   | 145.5 |
| 37.5° | 128.7 |
| 40°   | 113.0 |
| 42.5° | 100.2 |
| 45°   | 88.5  |
| 47.5° | 77.6  |
| 50°   | 68.8  |
| 52.5° | 60.9  |
| 55°   | 53.1  |
| 57.5° | 47.2  |
| 60°   | 41.3  |
| 62.5° | 35.4  |
| 65°   | 30.5  |
| 67.5° | 25.6  |
| 70°   | 21.6  |
| 72.5° | 17.7  |
| 75°   | 13.8  |
| 77.5° | 9.8   |
| 80°   | 6.9   |
| 82.5° | 3.9   |
| 85°   | 2.0   |
| 87.5° | 1.0   |
| 90°   | 0.0   |

(END OF REPORT)