

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1267069

Luminaire Tested: P3AS09R359735DE010 E3DLP1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1267069
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-17)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R359735DE010 E3DLP1H
Description: 3in Adjustable LED luminaire with, R35 optic, 3500K CCT AND, 97CRI , E3DLP1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 442.0 lumens
Efficiency: N/A
Efficacy: 39.8 lumens/watt
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.72
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1267069

CATALOG NUMBER: P3AS09R359735DE010 E3DLP1H

Luminous Intensity Polar Plot



TEST NUMBER: P1267069

CATALOG NUMBER: P3AS09R359735DE010 E3DLP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	97	93	97	94	91		94	92	89		91
3	102	95	90	86	100	94	89	85	91	87	84		89	85	82		86
4	97	89	83	79	95	88	82	78	86	81	77		84	80	77		82
5	92	83	77	73	90	82	77	73	81	76	72		79	75	71		77
6	87	78	72	68	86	77	72	68	76	71	67		75	70	67		73
7	83	74	68	63	82	73	67	63	72	67	63		71	66	63		69
8	79	70	64	60	78	69	63	59	68	63	59		67	62	59		66
9	76	66	60	56	75	66	60	56	65	59	56		64	59	56		63
10	72	63	57	53	71	62	57	53	61	56	53		61	56	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	142072
5°	138564
10°	126673
15°	107538
20°	85127
25°	64383
30°	46868
35°	31695
40°	19494
45°	11195
50°	6720
55°	5467
60°	4780
65°	4255
70°	3462
75°	3474
80°	3410
85°	3522

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 11195 cd/sqm

TEST NUMBER: P1267069

CATALOG NUMBER: P3AS09R359735DE010 E3DLP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	58.2	13.2
10°-20°	130.6	29.5
20°-30°	122.2	27.6
30°-40°	74.8	16.9
40°-50°	29.5	6.7
50°-60°	13.0	2.9
60°-70°	8.1	1.8
70°-80°	4.3	1.0
80°-90°	1.5	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	310.9	70.3
0°-40°	385.7	87.3
0°-60°	428.1	96.9
0°-90°	442.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	442.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	648	
5°	630	58
15°	474	131
25°	266	122
35°	118	75
45°	36	29
55°	14	13
65°	8	8
75°	4	4
85°	1	1
90°	0	

TEST NUMBER: P1267069

CATALOG NUMBER: P3AS09R359735DE010 E3DLP1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	647.9
1°	648.6
2°	646.5
3°	642.5
4°	636.3
5°	629.5
6°	620.7
7°	610.5
8°	598.2
9°	584.6
10°	568.9
11°	552.6
12°	534.9
13°	515.9
14°	494.8
15°	473.7
17.5°	419.2
20°	364.8
22.5°	312.4
25°	266.1
27.5°	223.2
30°	185.1
32.5°	149.7
35°	118.4
37.5°	90.5
40°	68.1
42.5°	49.0
45°	36.1
47.5°	25.9
50°	19.7
52.5°	16.3
55°	14.3
57.5°	12.3
60°	10.9
62.5°	9.5
65°	8.2
67.5°	6.8
70°	5.4
72.5°	4.8
75°	4.1
77.5°	3.4
80°	2.7
82.5°	2.0
85°	1.4
87.5°	0.7



TEST NUMBER: P1267069

CATALOG NUMBER: P3AS09R359735DE010 E3DLP1H

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)