

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1267583

Luminaire Tested: P3AS13R559735DE010 E3DL1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1267583
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-35)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R559735DE010 E3DL1H
Description: 3in Adjustable LED luminaire with, R55 optic, 3500K CCT AND, 97CRI , E3DL1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 987.0 lumens
Efficiency: N/A
Efficacy: 67.6 lumens/watt
Spacing Criteria (0/90/45): 0.83 / 0.83 / 0.81
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1267583

CATALOG NUMBER: P3AS13R559735DE010 E3DL1H

Luminous Intensity Polar Plot



TEST NUMBER: P1267583

CATALOG NUMBER: P3AS13R559735DE010 E3DL1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	108	106	104	104	103	101		101	99	98		97
2	108	103	99	95	106	101	97	94	98	95	92		95	92	90		92
3	102	96	91	87	100	95	90	86	92	88	85		89	86	84		87
4	97	90	84	80	95	89	83	79	86	82	78		84	81	78		82
5	92	84	78	74	91	83	78	74	81	77	73		80	76	72		78
6	88	79	73	69	86	78	73	68	77	72	68		75	71	68		74
7	84	74	68	64	82	74	68	64	72	67	64		71	67	63		70
8	80	70	64	60	78	70	64	60	69	63	60		67	63	60		67
9	76	66	61	57	75	66	60	56	65	60	56		64	59	56		63
10	73	63	57	53	72	62	57	53	62	57	53		61	56	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	271031
5°	268280
10°	259069
15°	239479
20°	206635
25°	163219
30°	115790
35°	74659
40°	44827
45°	25274
50°	13577
55°	4855
60°	4386
65°	4203
70°	4039
75°	3813
80°	3410
85°	2264

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 25274 cd/sqm

TEST NUMBER: P1267583

CATALOG NUMBER: P3AS13R559735DE010 E3DL1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	114.6	11.6
10°-20°	291.7	29.6
20°-30°	305.7	31.0
30°-40°	178.4	18.1
40°-50°	66.7	6.8
50°-60°	15.7	1.6
60°-70°	8.1	0.8
70°-80°	4.7	0.5
80°-90°	1.3	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	712.0	72.1
0°-40°	890.4	90.2
0°-60°	972.8	98.6
0°-90°	987.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	987.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1236	
5°	1219	115
15°	1055	292
25°	675	306
35°	279	178
45°	82	67
55°	13	16
65°	8	8
75°	4	5
85°	1	1
90°	0	

TEST NUMBER: P1267583

CATALOG NUMBER: P3AS13R559735DE010 E3DL1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	1236.0
2.5°	1232.3
5°	1218.8
7.5°	1197.0
10°	1163.5
12.5°	1116.4
15°	1054.9
17.5°	977.0
20°	885.5
22.5°	783.2
25°	674.6
27.5°	563.2
30°	457.3
32.5°	361.3
35°	278.9
37.5°	211.9
40°	156.6
42.5°	112.3
45°	81.5
47.5°	58.9
50°	39.8
52.5°	22.6
55°	12.7
57.5°	10.9
60°	10.0
62.5°	9.1
65°	8.1
67.5°	7.2
70°	6.3
72.5°	5.4
75°	4.5
77.5°	3.6
80°	2.7
82.5°	1.8
85°	0.9
87.5°	0.9
90°	0.0

(END OF REPORT)