

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1268143

Luminaire Tested: P3AS20R259735D010 E3DLP1H

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1268143  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-9)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS20R259735D010 E3DLP1H  
Description: 3in Adjustable LED luminaire with, R25 optic, 3500K CCT AND, 97CRI , E3DLP1H TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1009.9 lumens  
Efficiency: N/A  
Efficacy: 35.1 lumens/watt  
Spacing Criteria (0/90/45): 0.62 / 0.62 / 0.68  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 28.8  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1268143

CATALOG NUMBER: P3AS20R259735D010 E3DLP1H

### Luminous Intensity Polar Plot



TEST NUMBER: P1268143

CATALOG NUMBER: P3AS20R259735D010 E3DLP1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 108 | 105 | 111 | 108 | 106 | 104 | 104 | 102 | 101 |  | 100 | 99  | 98  |  | 97  |
| 2   | 107 | 102 | 98  | 95  | 105 | 101 | 97  | 94  | 97  | 94  | 92  |  | 94  | 92  | 90  |  | 92  |
| 3   | 102 | 95  | 90  | 86  | 100 | 94  | 89  | 86  | 91  | 87  | 84  |  | 89  | 86  | 83  |  | 87  |
| 4   | 97  | 89  | 84  | 79  | 95  | 88  | 83  | 79  | 86  | 81  | 78  |  | 84  | 80  | 77  |  | 82  |
| 5   | 92  | 84  | 78  | 74  | 91  | 83  | 77  | 73  | 81  | 76  | 73  |  | 79  | 75  | 72  |  | 78  |
| 6   | 88  | 79  | 73  | 69  | 86  | 78  | 72  | 68  | 77  | 72  | 68  |  | 75  | 71  | 67  |  | 74  |
| 7   | 84  | 74  | 68  | 64  | 82  | 74  | 68  | 64  | 72  | 67  | 64  |  | 71  | 67  | 63  |  | 70  |
| 8   | 80  | 70  | 65  | 60  | 79  | 70  | 64  | 60  | 69  | 64  | 60  |  | 68  | 63  | 60  |  | 67  |
| 9   | 76  | 67  | 61  | 57  | 75  | 66  | 61  | 57  | 65  | 60  | 57  |  | 65  | 60  | 57  |  | 64  |
| 10  | 73  | 64  | 58  | 54  | 72  | 63  | 58  | 54  | 62  | 57  | 54  |  | 62  | 57  | 54  |  | 61  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 366681 |
| 5°  | 351793 |
| 10° | 308188 |
| 15° | 247720 |
| 20° | 190323 |
| 25° | 144008 |
| 30° | 104067 |
| 35° | 69118  |
| 40° | 41907  |
| 45° | 24406  |
| 50° | 15590  |
| 55° | 12654  |
| 60° | 11052  |
| 65° | 9806   |
| 70° | 8078   |
| 75° | 7964   |
| 80° | 5935   |
| 85° | 7799   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 24406 cd/sqm

TEST NUMBER: P1268143

CATALOG NUMBER: P3AS20R259735D010 E3DLP1H

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 145.5  | 14.4      |
| 10°-20°   | 301.7  | 29.9      |
| 20°-30°   | 272.9  | 27.0      |
| 30°-40°   | 163.9  | 16.2      |
| 40°-50°   | 65.1   | 6.4       |
| 50°-60°   | 30.0   | 3.0       |
| 60°-70°   | 18.3   | 1.8       |
| 70°-80°   | 9.7    | 1.0       |
| 80°-90°   | 2.8    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 720.1  | 71.3      |
| 0°-40°    | 884.0  | 87.5      |
| 0°-60°    | 979.1  | 97.0      |
| 0°-90°    | 1009.9 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 1009.9 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 1672 |      |
| 5°  | 1598 | 145  |
| 15° | 1091 | 302  |
| 25° | 595  | 273  |
| 35° | 258  | 164  |
| 45° | 79   | 65   |
| 55° | 33   | 30   |
| 65° | 19   | 18   |
| 75° | 9    | 10   |
| 85° | 3    | 3    |
| 90° | 0    |      |

TEST NUMBER: P1268143

CATALOG NUMBER: P3AS20R259735D010 E3DLP1H

**CANDELA DISTRIBUTION (FULL):**

| 0°    |        |
|-------|--------|
| 0°    | 1672.2 |
| 1°    | 1672.2 |
| 2°    | 1664.3 |
| 3°    | 1647.0 |
| 4°    | 1625.0 |
| 5°    | 1598.2 |
| 6°    | 1563.6 |
| 7°    | 1524.2 |
| 8°    | 1478.5 |
| 9°    | 1432.9 |
| 10°   | 1384.1 |
| 11°   | 1327.4 |
| 12°   | 1269.1 |
| 13°   | 1210.9 |
| 14°   | 1152.6 |
| 15°   | 1091.2 |
| 17.5° | 946.3  |
| 20°   | 815.6  |
| 22.5° | 697.5  |
| 25°   | 595.2  |
| 27.5° | 499.1  |
| 30°   | 411.0  |
| 32.5° | 330.7  |
| 35°   | 258.2  |
| 37.5° | 196.8  |
| 40°   | 146.4  |
| 42.5° | 107.1  |
| 45°   | 78.7   |
| 47.5° | 59.8   |
| 50°   | 45.7   |
| 52.5° | 37.8   |
| 55°   | 33.1   |
| 57.5° | 28.3   |
| 60°   | 25.2   |
| 62.5° | 20.5   |
| 65°   | 18.9   |
| 67.5° | 15.7   |
| 70°   | 12.6   |
| 72.5° | 11.0   |
| 75°   | 9.4    |
| 77.5° | 7.9    |
| 80°   | 4.7    |
| 82.5° | 3.1    |
| 85°   | 3.1    |
| 87.5° | 1.6    |



TEST NUMBER: P1268143

CATALOG NUMBER: P3AS20R259735D010 E3DLP1H

CANDELA DISTRIBUTION (continued):



(END OF REPORT)