

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1268367

Luminaire Tested: P3AS20R659735D010 E3DL1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1268367
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-41)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS20R659735D010 E3DL1WH
Description: 3in Adjustable LED luminaire with, R65 optic, 3500K CCT AND, 97CRI , E3DL1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1091.0 lumens
Efficiency: N/A
Efficacy: 37.9 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1268367

CATALOG NUMBER: P3AS20R659735D010 E3DL1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1268367

CATALOG NUMBER: P3AS20R659735D010 E3DL1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	110	108	105	103	104	102	100		100	98	97		96
2	107	101	97	93	104	100	96	92	96	93	90		93	91	88		90
3	101	94	88	84	99	92	87	83	90	85	82		87	84	81		85
4	95	87	81	76	93	86	80	76	84	79	75		82	78	74		80
5	90	81	75	70	88	80	74	70	78	73	69		77	72	69		75
6	85	76	69	65	84	75	69	65	73	68	64		72	67	64		71
7	81	71	65	60	79	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	57	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	53	49		57	52	49		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	277324
5°	270415
10°	251832
15°	225677
20°	194897
25°	162130
30°	127842
35°	94736
40°	65294
45°	40500
50°	22004
55°	13839
60°	11710
65°	10585
70°	9104
75°	7964
80°	7956
85°	7799

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 40500 cd/sqm

TEST NUMBER: P1268367

CATALOG NUMBER: P3AS20R659735D010 E3DL1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	114.2	10.5
10°-20°	276.3	25.3
20°-30°	305.5	28.0
30°-40°	221.9	20.3
40°-50°	104.0	9.5
50°-60°	35.0	3.2
60°-70°	20.2	1.9
70°-80°	10.6	1.0
80°-90°	3.4	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	695.9	63.8
0°-40°	917.8	84.1
0°-60°	1056.8	96.9
0°-90°	1091.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1091.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1265	
5°	1228	114
15°	994	276
25°	670	306
35°	354	222
45°	131	104
55°	36	35
65°	20	20
75°	9	11
85°	3	3
90°	0	

TEST NUMBER: P1268367

CATALOG NUMBER: P3AS20R659735D010 E3DL1WH

CANDELA DISTRIBUTION (FULL):

	0°
0°	1264.7
2.5°	1256.8
5°	1228.5
7.5°	1186.0
10°	1131.0
12.5°	1066.5
15°	994.1
17.5°	915.5
20°	835.2
22.5°	751.9
25°	670.1
27.5°	586.7
30°	504.9
32.5°	426.3
35°	353.9
37.5°	287.9
40°	228.1
42.5°	174.6
45°	130.6
47.5°	94.4
50°	64.5
52.5°	44.0
55°	36.2
57.5°	31.5
60°	26.7
62.5°	23.6
65°	20.4
67.5°	17.3
70°	14.2
72.5°	12.6
75°	9.4
77.5°	7.9
80°	6.3
82.5°	4.7
85°	3.1
87.5°	1.6
90°	0.0

(END OF REPORT)