

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1268543

Luminaire Tested: P3AS02R159740DE010 E3DLP1MW

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1268543
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-1)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R159740DE010 E3DLP1MW
Description: 3in Adjustable LED luminaire with, R15 optic, 4000K CCT AND, 97CRI , E3DLP1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 145.0 lumens
Efficiency: N/A
Efficacy: 40.3 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.61
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1268543

CATALOG NUMBER: P3AS02R159740DE010 E3DLP1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1268543

CATALOG NUMBER: P3AS02R159740DE010 E3DLP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	106	111	108	106	104	104	102	101		100	99	98		97
2	108	103	98	95	105	101	97	94	98	95	92		95	92	90		92
3	102	96	91	87	100	94	90	86	92	88	85		89	86	83		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	78		82
5	93	84	78	74	91	83	78	74	81	77	73		80	76	73		78
6	88	79	73	69	87	79	73	69	77	72	69		76	71	68		74
7	84	75	69	65	83	74	69	65	73	68	64		72	67	64		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		68
9	77	68	62	58	76	67	62	58	66	61	58		65	61	57		64
10	74	64	59	55	73	64	59	55	63	58	55		62	58	55		62

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	62517
5°	57781
10°	46136
15°	34847
20°	26532
25°	20227
30°	14483
35°	9450
40°	5782
45°	3504
50°	2320
55°	1797
60°	1535
65°	1349
70°	1218
75°	1186
80°	884
85°	503

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3504 cd/sqm

TEST NUMBER: P1268543

CATALOG NUMBER: P3AS02R159740DE010 E3DLP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	23.3	16.0
10°-20°	42.9	29.6
20°-30°	38.2	26.3
30°-40°	22.6	15.6
40°-50°	9.3	6.4
50°-60°	4.4	3.0
60°-70°	2.7	1.8
70°-80°	1.4	0.9
80°-90°	0.3	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	104.4	72.0
0°-40°	127.0	87.6
0°-60°	140.6	97.0
0°-90°	145.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	145.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	285	
5°	262	23
15°	154	43
25°	84	38
35°	35	23
45°	11	9
55°	5	4
65°	3	3
75°	1	1
85°	0	0
90°	0	

TEST NUMBER: P1268543

CATALOG NUMBER: P3AS02R159740DE010 E3DLP1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	285.1
1°	284.4
2°	282.3
3°	278.1
4°	271.0
5°	262.5
6°	253.4
7°	242.5
8°	231.2
9°	219.7
10°	207.2
12.5°	178.7
15°	153.5
17.5°	131.9
20°	113.7
22.5°	97.7
25°	83.6
27.5°	69.9
30°	57.2
32.5°	45.7
35°	35.3
37.5°	27.1
40°	20.2
42.5°	15.1
45°	11.3
47.5°	8.7
50°	6.8
52.5°	5.7
55°	4.7
57.5°	4.0
60°	3.5
62.5°	3.1
65°	2.6
67.5°	2.4
70°	1.9
72.5°	1.6
75°	1.4
77.5°	0.9
80°	0.7
82.5°	0.5
85°	0.2
87.5°	0.2
90°	0.0

(END OF REPORT)