

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1269066

Luminaire Tested: P3AS05R359740DE010 E3DLD1MW

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1269066  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-18)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS05R359740DE010 E3DLD1MW  
Description: 3in Adjustable LED luminaire with, R35 optic, 4000K CCT AND, 97CRI , E3DLD1MW TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 392.0 lumens  
Efficiency: N/A  
Efficacy: 54.4 lumens/watt  
Spacing Criteria (0/90/45): 0.8 / 0.8 / 0.87  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 7.2  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1269066

CATALOG NUMBER: P3AS05R359740DE010 E3DLD1MW

### Luminous Intensity Polar Plot



TEST NUMBER: P1269066

CATALOG NUMBER: P3AS05R359740DE010 E3DLD1MW

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 112 | 109 | 106 | 104 | 110 | 107 | 104 | 102 | 103 | 101 | 99  |  | 99  | 98  | 96  |  | 96  |
| 2   | 106 | 100 | 96  | 92  | 104 | 98  | 94  | 91  | 95  | 92  | 89  |  | 92  | 89  | 87  |  | 89  |
| 3   | 100 | 92  | 87  | 82  | 98  | 91  | 86  | 81  | 88  | 84  | 80  |  | 86  | 82  | 79  |  | 83  |
| 4   | 94  | 85  | 79  | 74  | 92  | 84  | 78  | 74  | 82  | 77  | 73  |  | 80  | 75  | 72  |  | 78  |
| 5   | 89  | 79  | 73  | 68  | 87  | 78  | 72  | 67  | 76  | 71  | 67  |  | 75  | 70  | 66  |  | 73  |
| 6   | 84  | 74  | 67  | 62  | 82  | 73  | 67  | 62  | 71  | 66  | 61  |  | 70  | 65  | 61  |  | 68  |
| 7   | 79  | 69  | 62  | 57  | 78  | 68  | 62  | 57  | 67  | 61  | 57  |  | 65  | 60  | 57  |  | 64  |
| 8   | 75  | 64  | 58  | 53  | 74  | 64  | 57  | 53  | 63  | 57  | 53  |  | 62  | 56  | 53  |  | 61  |
| 9   | 71  | 60  | 54  | 50  | 70  | 60  | 54  | 50  | 59  | 53  | 49  |  | 58  | 53  | 49  |  | 57  |
| 10  | 67  | 57  | 51  | 46  | 66  | 56  | 50  | 46  | 56  | 50  | 46  |  | 55  | 50  | 46  |  | 54  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |       |
|-----|-------|
|     | 0°    |
| 0°  | 89554 |
| 5°  | 87651 |
| 10° | 82074 |
| 15° | 73689 |
| 20° | 64102 |
| 25° | 54608 |
| 30° | 45754 |
| 35° | 36433 |
| 40° | 26335 |
| 45° | 16684 |
| 50° | 9074  |
| 55° | 6308  |
| 60° | 5964  |
| 65° | 5552  |
| 70° | 5257  |
| 75° | 4490  |
| 80° | 4293  |
| 85° | 3774  |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 16684 cd/sqm

TEST NUMBER: P1269066

CATALOG NUMBER: P3AS05R359740DE010 E3DLD1MW

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 37.1   | 9.5       |
| 10°-20°   | 90.3   | 23.0      |
| 20°-30°   | 103.5  | 26.4      |
| 30°-40°   | 84.4   | 21.5      |
| 40°-50°   | 42.6   | 10.9      |
| 50°-60°   | 15.8   | 4.0       |
| 60°-70°   | 10.6   | 2.7       |
| 70°-80°   | 5.9    | 1.5       |
| 80°-90°   | 1.8    | 0.5       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 230.9  | 58.9      |
| 0°-40°    | 315.3  | 80.4      |
| 0°-60°    | 373.8  | 95.3      |
| 0°-90°    | 392.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 392.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 408 |      |
| 5°  | 398 | 37   |
| 15° | 325 | 90   |
| 25° | 226 | 104  |
| 35° | 136 | 84   |
| 45° | 54  | 43   |
| 55° | 16  | 16   |
| 65° | 11  | 11   |
| 75° | 5   | 6    |
| 85° | 2   | 2    |
| 90° | 0   |      |

TEST NUMBER: P1269066

CATALOG NUMBER: P3AS05R359740DE010 E3DLD1MW

**CANDELA DISTRIBUTION (FULL):**

| 0°    |       |
|-------|-------|
| 0°    | 408.4 |
| 1°    | 407.9 |
| 2°    | 406.9 |
| 3°    | 405.0 |
| 4°    | 402.1 |
| 5°    | 398.2 |
| 6°    | 393.3 |
| 7°    | 388.5 |
| 8°    | 382.2 |
| 9°    | 375.9 |
| 10°   | 368.6 |
| 11°   | 360.9 |
| 12°   | 352.6 |
| 13°   | 343.4 |
| 14°   | 333.8 |
| 15°   | 324.6 |
| 17.5° | 299.8 |
| 20°   | 274.7 |
| 22.5° | 249.0 |
| 25°   | 225.7 |
| 27.5° | 203.0 |
| 30°   | 180.7 |
| 32.5° | 158.4 |
| 35°   | 136.1 |
| 37.5° | 113.8 |
| 40°   | 92.0  |
| 42.5° | 71.7  |
| 45°   | 53.8  |
| 47.5° | 38.8  |
| 50°   | 26.6  |
| 52.5° | 19.4  |
| 55°   | 16.5  |
| 57.5° | 15.0  |
| 60°   | 13.6  |
| 62.5° | 12.1  |
| 65°   | 10.7  |
| 67.5° | 9.2   |
| 70°   | 8.2   |
| 72.5° | 6.8   |
| 75°   | 5.3   |
| 77.5° | 4.4   |
| 80°   | 3.4   |
| 82.5° | 2.4   |
| 85°   | 1.5   |
| 87.5° | 1.0   |



TEST NUMBER: P1269066  
CATALOG NUMBER: P3AS05R359740DE010 E3DLD1MW

CANDELA DISTRIBUTION (continued):

0°  
90° | 0.0

(END OF REPORT)