

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1269473

Luminaire Tested: P3AS09R409740DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1269473
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-22)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R409740DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R40 optic, 4000K CCT AND, 97CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 310.0 lumens
Efficiency: N/A
Efficacy: 27.9 lumens/watt
Spacing Criteria (0/90/45): 0.83 / 0.83 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1269473

CATALOG NUMBER: P3AS09R409740DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1269473

CATALOG NUMBER: P3AS09R409740DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	98	96		96
2	106	100	96	92	104	98	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	81	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	75	72		78
5	89	79	73	68	87	78	72	67	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	61		70	65	61		68
7	79	69	62	57	78	68	62	57	67	61	57		65	60	57		64
8	75	64	58	53	74	64	58	53	63	57	53		62	56	53		61
9	71	60	54	50	70	60	54	50	59	53	49		58	53	49		57
10	67	57	51	46	66	56	50	46	56	50	46		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	69578
5°	68325
10°	64417
15°	58502
20°	51384
25°	43890
30°	36360
35°	28027
40°	19952
45°	13459
50°	7335
55°	5161
60°	4868
65°	4514
70°	3975
75°	3813
80°	3031
85°	2516

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 13459 cd/sqm

TEST NUMBER: P1269473

CATALOG NUMBER: P3AS09R409740DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	29.0	9.3
10°-20°	71.8	23.2
20°-30°	83.0	26.8
30°-40°	65.4	21.1
40°-50°	33.6	10.8
50°-60°	12.8	4.1
60°-70°	8.5	2.7
70°-80°	4.6	1.5
80°-90°	1.4	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	183.7	59.3
0°-40°	249.1	80.4
0°-60°	295.5	95.3
0°-90°	310.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	310.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	317	
5°	310	29
15°	258	72
25°	181	83
35°	105	65
45°	43	34
55°	14	13
65°	9	8
75°	4	5
85°	1	1
90°	0	

TEST NUMBER: P1269473

CATALOG NUMBER: P3AS09R409740DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	317.3
2.5°	315.6
5°	310.4
7.5°	301.4
10°	289.3
12.5°	275.0
15°	257.7
17.5°	239.7
20°	220.2
22.5°	200.5
25°	181.4
27.5°	162.3
30°	143.6
32.5°	124.5
35°	104.7
37.5°	86.4
40°	69.7
42.5°	55.5
45°	43.4
47.5°	31.6
50°	21.5
52.5°	15.6
55°	13.5
57.5°	12.1
60°	11.1
62.5°	9.7
65°	8.7
67.5°	7.3
70°	6.2
72.5°	5.2
75°	4.5
77.5°	3.5
80°	2.4
82.5°	2.1
85°	1.0
87.5°	0.7
90°	0.0

(END OF REPORT)