

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1269852

Luminaire Tested: P3AS13R359740DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1269852
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-18)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R359740DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R35 optic, 4000K CCT AND, 97CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 373.0 lumens
Efficiency: N/A
Efficacy: 25.5 lumens/watt
Spacing Criteria (0/90/45): 0.8 / 0.8 / 0.87
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1269852

CATALOG NUMBER: P3AS13R359740DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1269852

CATALOG NUMBER: P3AS13R359740DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	98	96		96
2	106	100	96	92	104	98	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	81	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	75	72		78
5	89	79	73	68	87	78	72	67	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	61		70	65	61		68
7	79	69	62	57	78	68	62	57	67	61	57		65	60	57		64
8	75	64	58	53	74	64	57	53	63	57	53		62	56	53		61
9	71	60	54	50	70	60	54	50	59	53	49		58	53	49		57
10	67	57	51	46	66	56	50	46	56	50	46		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	85212
5°	83403
10°	78110
15°	70103
20°	60975
25°	51971
30°	43526
35°	34666
40°	25076
45°	15878
50°	8665
55°	6002
60°	5657
65°	5241
70°	5001
75°	4321
80°	4041
85°	3522

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15878 cd/sqm

TEST NUMBER: P1269852

CATALOG NUMBER: P3AS13R359740DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	35.3	9.5
10°-20°	85.9	23.0
20°-30°	98.5	26.4
30°-40°	80.4	21.5
40°-50°	40.5	10.9
50°-60°	15.1	4.0
60°-70°	10.1	2.7
70°-80°	5.6	1.5
80°-90°	1.7	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	219.7	58.9
0°-40°	300.0	80.4
0°-60°	355.6	95.3
0°-90°	373.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	373.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	389	
5°	379	35
15°	309	86
25°	215	98
35°	130	80
45°	51	41
55°	16	15
65°	10	10
75°	5	6
85°	1	2
90°	0	

TEST NUMBER: P1269852

CATALOG NUMBER: P3AS13R359740DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	388.6
1°	388.1
2°	387.2
3°	385.3
4°	382.6
5°	378.9
6°	374.3
7°	369.7
8°	363.7
9°	357.7
10°	350.8
11°	343.4
12°	335.6
13°	326.8
14°	317.6
15°	308.8
17.5°	285.3
20°	261.3
22.5°	236.9
25°	214.8
27.5°	193.1
30°	171.9
32.5°	150.7
35°	129.5
37.5°	108.3
40°	87.6
42.5°	68.2
45°	51.2
47.5°	36.9
50°	25.4
52.5°	18.4
55°	15.7
57.5°	14.3
60°	12.9
62.5°	11.5
65°	10.1
67.5°	8.8
70°	7.8
72.5°	6.5
75°	5.1
77.5°	4.1
80°	3.2
82.5°	2.3
85°	1.4
87.5°	0.9



TEST NUMBER: P1269852

CATALOG NUMBER: P3AS13R359740DE010 E3DLD1GPH

CANDELA DISTRIBUTION (continued):



(END OF REPORT)