

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1269938

Luminaire Tested: P3AS13R509740DE010 E3DLD1GPH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1269938
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-30)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R509740DE010 E3DLD1GPH
Description: 3in Adjustable LED luminaire with, R50 optic, 4000K CCT AND, 97CRI , E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 404.0 lumens
Efficiency: N/A
Efficacy: 27.7 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.93
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1269938

CATALOG NUMBER: P3AS13R509740DE010 E3DLD1GPH

Luminous Intensity Polar Plot



TEST NUMBER: P1269938

CATALOG NUMBER: P3AS13R509740DE010 E3DLD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	102	103	101	99		99	97	96		95
2	106	100	95	91	103	98	94	90	95	91	88		92	89	86		89
3	99	92	86	81	97	90	85	81	88	83	79		85	81	78		83
4	93	85	78	73	91	83	77	73	81	76	72		79	75	71		77
5	88	78	72	67	86	77	71	66	75	70	66		74	69	65		72
6	83	73	66	61	81	72	65	61	70	65	60		69	64	60		67
7	78	68	61	56	77	67	61	56	66	60	56		64	59	55		63
8	74	63	57	52	73	63	56	52	61	56	52		60	55	51		59
9	70	59	53	48	69	59	52	48	58	52	48		57	52	48		56
10	66	56	49	45	65	55	49	45	54	49	45		54	48	45		53

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	82099
5°	80893
10°	77309
15°	71601
20°	64336
25°	56568
30°	48109
35°	39003
40°	29312
45°	18886
50°	8972
55°	7034
60°	6666
65°	6226
70°	5642
75°	5083
80°	4672
85°	4529

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 18886 cd/sqm

TEST NUMBER: P1269938

CATALOG NUMBER: P3AS13R509740DE010 E3DLD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	34.4	8.5
10°-20°	87.9	21.8
20°-30°	106.8	26.4
30°-40°	90.6	22.4
40°-50°	47.1	11.7
50°-60°	17.0	4.2
60°-70°	11.7	2.9
70°-80°	6.4	1.6
80°-90°	2.0	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	229.2	56.7
0°-40°	319.8	79.2
0°-60°	383.9	95.0
0°-90°	404.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	404.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	374	
5°	368	34
15°	315	88
25°	234	107
35°	146	91
45°	61	47
55°	18	17
65°	12	12
75°	6	6
85°	2	2
90°	0	

TEST NUMBER: P1269938

CATALOG NUMBER: P3AS13R509740DE010 E3DLD1GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	374.4
2.5°	373.0
5°	367.5
7.5°	359.2
10°	347.2
12.5°	332.0
15°	315.4
17.5°	296.5
20°	275.7
22.5°	254.5
25°	233.8
27.5°	212.1
30°	190.0
32.5°	167.8
35°	145.7
37.5°	124.0
40°	102.4
42.5°	81.6
45°	60.9
47.5°	40.6
50°	26.3
52.5°	20.3
55°	18.4
57.5°	16.6
60°	15.2
62.5°	13.4
65°	12.0
67.5°	10.1
70°	8.8
72.5°	7.4
75°	6.0
77.5°	4.6
80°	3.7
82.5°	2.8
85°	1.8
87.5°	0.9
90°	0.0

(END OF REPORT)